
BC+600 MAX

BC/6 OR 100 MIN


ALTERNATIVE CONCRETE PIPE PROTECTION FOR COVER LESS THAT 900 (1200 UNDER HIGHWAYS)

RISING MAIN


NON HIGHWAYS AREAS | HIGHWAYS



DUAL PIPE TRENCH BEDDING DETAIL







300

150

175

175 THICK GEN3

- CONCRETE SLAB

A393 MESH WITH

- 50mm TOP COVER

TYPE 1 - GRANULAR FILL

_ CARRIAGEWAY CONSTRUCTION

BC









SELECTED SIDEFILL AND SURROUND.

GRANULAR MATERIAL TO SHW CLAUSE 503.300

DN = NOMINAL INTERNAL DIAMETER OF PIPE.

BC = OUTSIDE DIAMETER OF PIPE.

CONCRETE BED AND SURROUND CLASS 'Z'





ST4 CONCRETE BED AND SURROUND.

DIMENSION Y

CLASS	MACHINE DUG UNIFORM SOIL ROCK OR MIXED SOILS	ROCK OR MIXED SOILS
1,F,B & S	NOTE (i)	NOTE (ii)
. & Z	NOTE (ii)	NOTE (ii)

(i) Y=BC/6, WITH MIN 100 UNDER BARRELS (50 FOR SLEEVE JOINTED) AND MIN 50 UNDER SOCKETS, WHICHEVER IS THE GREATER, WITH MAX OF 400.

(ii) Y=BC/4, WITH MIN 200 UNDER BARRELS (150 FOR SLEEVE JOINTED) AND MIN 150 UNDER SOCKETS, WHICHEVER IS THE GREATER, WITH A MAX OF 400.

1903-SD-101

ᆯ

January 2008

1.20

도

Σ

BC 150

 $\boldsymbol{6}.$ CLAY OR CONCRETE STANKS TO BE ADDED AS SHOWN ON SEWER LONG SECTIONS.

5. CLAUSE NUMBERS REFER TO SHW (SPECIFICATION HIGHWAY WORKS) LATEST EDITION.

4. TOPSOIL THICKNESS TO BE AS EXISTING, BUT NOT LESS THAN 150 3. REFER TO STANDARD DETAIL 1903/SD/100 (DRAINAGE NOTES) NOTES $\begin{array}{c} \text{DO NOT SCALE} \\ \text{1. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS OTHERWISE STATED.} \end{array}$

2. PIPE BEDDING CLASSIFICATIONS ARE DERIVED FROM T.R.R.L. DOCUMENT 'SIMPLIFIED TABLES OF EXTERNAL LOADS ON BURIED PIPELINES.'

03/12/08 30/05/08 DATE P 宔 FOR TECHNICAL APPROVAL FIRST ISSUE ISSUED FOR TECHNICAL APPROVAL DESCRIPTION 웆

REV

BC+600 MAX

Mountbatten House, Basing View, Basingstoke, Hampshire RG21 4HJ Tel: +44 (0)1256 318800 Fax: +44 (0)1256 318700 http://www.wspgroup.com

COUNTRYSIDE PROPERTIES

SOUTH WEST BICESTER

BICESTER, OXFORDSHIRE

()	11011903
WSP Group plc	1903/SD/101
	В