



CONCRETE OR MORTAR SURROUNDS TO ACCESS COVER SHALL NOT BE USED ON THESE WORKS.

DO NOT SCALE

- NOTES:
1. ALL DIMENSIONS ARE IN MILLIMETRES UNLESS OTHERWISE STATED.
 2. ALL CLAUSE NUMBERS REFER TO SPECIFICATION FOR HIGHWAY WORKS.
 3. CONCRETE BLOCKS TO BE 80mm THICK AND COMPLY WITH THE REQUIREMENTS OF BS EN 1338:2003.
 4. BLOCKS SHOULD BE LAID IN ACCORDANCE WITH CLAUSE 1107 AND BS 7533 PART 3.
 5. ALL BLOCKS TO BE TRIMMED SHALL BE CUT USING HYDRAULIC / MECHANICAL SPLITTERS OR A BENCH MOUNTED SAW WITH DUST SUPPRESSION/EXTRACTION SYSTEM.
 6. WHERE THE TRIMMING OF BLOCKS IS NECESSARY, PORTIONS OF LESS THAN ONE THIRD OF AN ENTIRE BLOCK SHALL NOT BE LAID. INSTEAD THE PATTERN SHOULD BE ALTERED TO ENABLE LARGER PIECES OF BLOCK TO BE USED.
 7. BLOCKS BEDDED ON EPOXY MORTAR SHOULD HAVE THE TOP 30mm OF THEIR VERTICAL JOINTS RAKED OUT AND RE-POINTED WITH DESIGNATION (1) CEMENT/SAND MORTAR TO CLAUSE 2404.

8. TYPICAL UNIT WEIGHTS:
 CONCRETE PAVER: 200x100x80 3.7kg
 240x160x80 7.1kg
 240x320x80 14.1kg

REV	DATE	BY	DESCRIPTION	CHK	APP
C	03/12/08	JH	ISSUED FOR TECHNICAL APPROVAL	JAW	JH
B	24/11/08	DP	REMOVED CONCRETE SURROUND DETAIL	-	JAW
A	16/09/08	DP	FIRST ISSUE	LH	JM

FOR TECHNICAL APPROVAL

WSP

Mountbatten House, Basing View, Basingstoke, Hampshire RG21 4HJ
 Tel: +44 (0)1256 318800 Fax: +44 (0)1256 318700
 http://www.wspgroup.com

COUNTRYSIDE PROPERTIES

PROJECT: SOUTH WEST BICESTER
 BICESTER, OXFORDSHIRE

ON SITE WORKS
 BLOCK PAVING DETAILS

SCALE @ AS:	CHECKED:	APPROVED:
N.T.S.	LH	JM

CAD FILE:	DESIGN/DRAWN:	DATE:
1903-SD-206	PJ	January 2008

PROJECT NO: 11011903
 DRAWING NO: 1903/SD/206
 REV: C

WSP Group plc