

- Key - External Finishes:**
- Red Brick: Leicester autumn multi stock
 - Recon Stone: Atlas Rustic Old Cotswold Stone
 - Render: Weber Cream
 - Render: Weber Cornish
 - Render: Weber Silver Pearl
- Roof Tiles:**
- Brown Clay Plain Tiles: Sandtoft 20/20, Tuscan
 - Brindle Red Plain Tiles: Marley Eternit Plain Tile, Moss Red
 - Reconstructed slate: Marley Eternit Rivendale Fibre Cement Slate, Blue-Black

- Key - Boundary Treatments:**
- 2m High close board fence
 - 0.6m High dwarf artificial stone wall with halfround ridge tile coping
 - 1.8m High close boarded fencing
 - 1.8m High masonry wall with brick on edge finish
 - 1.5m High masonry wall with 0.3m trellis
 - Red Brick
 - Recon Stone
 - Render (to match building)
 - 1.2m High metal railings
 - Timber knee rail

NOTES
 CONTRACTORS MUST VERIFY ALL DIMENSIONS ON SITE BEFORE COMMENCING ANY WORK ON SHOP DRAWINGS
 DO NOT SCALE FROM THIS DRAWING
 MCBAINS COOPER CONSULTING LTD COPYRIGHT

265.00

69.20

16.40

REV	AMENDMENT	DATE	CHKD
I	Boundary treatments amended	31.03.2014	LB
H	Knee rails amended	16.01.2014	PO'R
G	Walling types amended: buff brick omitted Reconstructed slate type amended	22.08.2013	PO'R
F	Boundary Fence to NE updated	20.08.2013	PO'R
E	Materials Specification confirmed / updated	26.04.2013	PO'R
D	Drawing updated to suit layout updates	23.04.2013	PO'R
C	Drawing updated to suit planning comments	12.12.2012	PO'R
B	Minor materials amendments, drawing advanced to Planning Status.	12.12.2012	PO'R
A	Minor materials amendments to suit plan revisions.	04.12.2012	PO'R

DRAWING STATUS: **PLANNING**

Notes:

- Cast stone details - Portland colour.
- Windows - White PVCu.
- Flue extracts to boilers must not be used on front elevations.
- Brick walls to be either English or Flemish bond
- Proprietary tile terminator is to be used to match roof tiles.
- Weepholes area to be kept to a minimum & matching with brickwork.
- Vertical expansion joints to be located behind downpipes.
- Where render is used, lintels, cills & features to be expressed.
- All timber gates to be dark stained timber.
- All vertical cheeks of dormers to be lead clad.
- All garage doors to be pressed steel
- All upper floor mechanical vents and soil vent pipes to be extracted through ridge vent tiles to match roof tile.
- On stone and brick buildings, window reveals should be a minimum 50mm where there is no sub-cill.
- Gutters must be mounted directly on walls, sprockets or rafter feet.
- Rainwater goods should be black coloured.

Calculations:


External finishing materials confirmed to the percentage breakdown as stated in the Code Directive.

Urban Village: (16)

- Render - 8 units - 50%
- Red Facing Brick - 8 units - 50%
- Artificial slate tiles - 10 units = 70%
- Brindle red plain tiles - 8 units - 30%

Whitelands: (125)

- Render - 74 units - 60%
- Cotswold Facing Stone - 26 units - 20%
- Red Facing Brick - 25 units - 20%
- Artificial slate tiles - 62 units = 50%
- Brindle red plain tiles - 42 units - 35%
- Plain Clay tiles - 21 units - 15%



MCBAINS COOPER CONSULTING LTD.
 SEACOURT TOWER WEST WAY OXFORD OX2 0JJ
 TELEPHONE: 01865 240 244 FACSIMILE: 01865 790 571

CLIENT
 BELLWAY HOMES LTD.
 (NORTHERN HOME COUNTIES)

PROJECT
 KINGSMERE PLOTS KM7 & KM9
 BICESTER, OXFORDSHIRE

DRAWING TITLE
 BUILDING MATERIALS &
 BOUNDARY TREATMENTS PLAN

ARCHITECTURE

SCALE: 1:500 @ A1
 1:1000 @ A3
 DRAWN BY: KC/TG
 CHECKED: PO'R
 DATE: AUG 13

DRAWING NUMBER: **ar 56234 -104**
 REVISION: 1