

Roof pitch: 40°

Eaves to be constructed in accordance with eaves detail.

Entrance door style 1

Entrance canopy style 1.

Facing brick to all elevations as Indicated: to be constructed in accordance with manufacturer's recommendations and structural engineer's design.

Leaded light windows to all elevations

Brick heads and cills to all elevations

Provide Code 4 leadwork flashing with cavity tray over to all Refer to site general door and window schedule for details.

Refer to development engineers site layout for locations of ramp / steps. Provide stepped DPC 150mm above top of threshold. All entrance doors to have flush threhold and internal transition strip to suit mobility standards in accordance with Approved Document M, refer to standard detail SUP/DPC/LT.

Movement joints in accordance with Structural Engineers requirements.

Additionally safety glazing will also be required if within 800mm of finished floor level. *NOTE:
If upper floor openable window is within 800mm of floor, internal guarding will be required in accordance with standard detail INT/WG/1.

Ret	Date	Details
Э	05/01/17	7 BT Customer splice point shown as client's markup
В	31/10/16	31/10/16 Entrance door style corrected.
 A	03/10/16	03/10/16 Gas meter box design amended.

BELLWAY HOMES NORTHERN-HOME-COUNTIES MILTON-KEYNES

AF3 - D FRONT ELEVATION

Site Location KINGSMERE KM5 & KM22
BICESTER

SHEET 5 of 12

Scale	1.50	Date 08 02 16
Drawing No. 113/410	113/410	Rev. C
Drawn By	CDA	Checked By. CDA
Cad Ref:		



HANDING AS OPP

HANDINGS
3 PLOTS
74
73