

Sign ref.	TSRGD ref.	Sign face				Material Class	Mounting height (mm)	Supports					Foundation(s)				Foundation Type A or B	Setback (mm)	Notes		
		Width (mm)	Height (mm)	Area (m <sup>2</sup> )	X-Height (mm)			No.	Type	Post Diameter and Wall Thickness	Length (mm)	Post Centre	Illuminated	Passive safety	No.	Depth (mm)				Width (mm)	Length (mm)
A4-01	2703	950	730	0.69	60.00	RA2	2100	1	Steel circular section S275	76.1mm O.D. 4mm thick	3580	n/a	✓	1	600	900	900	150	A	600	Approx.45m in advance of junction
A4-02	2703	950	730	0.69	60.00	RA2	2100	1	Steel circular section S275	76.1mm O.D. 4mm thick	3580	n/a	✓	1	600	900	900	150	A	back of footpath	Approx.25m in advance of junction
A4-03	2703	950	730	0.69	60.00	RA2	2100	1	Steel circular section S275	76.1mm O.D. 4mm thick	3580	n/a	✓	1	600	900	900	150	A	back of footpath	Approx.54m in advance of junction
A4-04	2703	1580	1215	1.92	100.00	RA2	2000	2	Steel circular section S275	88.9mm O.D. 4mm thick	3965	882	✓	1	600	1300	1300	150	B	1200	in verge
A4-05	S13.9	1145	1885	2.16	100.00	RA2	2000	2	Steel circular section S275	88.9mm O.D. 5mm thick	4635	n/a	✓	1	600	1100	1500	150	B	1200	Approx. 150m in advance of junction
A4-06	7301 (Non-Pres. Variant)	1050	750	0.78	n/a	RA2	2000	1	Steel circular section S275	76.1mm O.D. 4mm thick	3500	n/a	✓	1	600	900	1000	150	A	1200	in verge at the junction
A4-07	7301 (Non-Pres. Variant)	1050	750	0.78	n/a	RA2	2000	1	Steel circular section S275	76.1mm O.D. 4mm thick	3500	n/a	✓	1	600	900	1000	150	A	1200	in verge at the junction
A4-08	2703	1580	1215	1.92	100.00	RA2	2000	2	Steel circular section S275	88.9mm O.D. 4mm thick	3965	882	✓	1	600	1300	1300	150	B	1200	Approx.225m in advance of junction
A4-09	7306	1340	1565	2.10	100.00	RA2	2000	2	Steel circular section S275	88.9mm O.D. 4mm thick	4315	732	✓	1	600	1200	1400	150	B	1200	Approx. 150 yards (137m) in advance of junction
A4-10	2703	1435	600	0.86	100.00	RA2	2000	2	Steel circular section S275	76.1mm O.D. 3.2mm thick	3350	807	✓	1	600	1200	900	150	B	1200	Approx.225m in advance of junction
A4-11	7301 (Non-Pres. Variant)	1050	750	0.78	n/a	RA2	2000	1	Steel circular section S275	76.1mm O.D. 4mm thick	3500	n/a	✓	1	600	900	1000	150	A	1200	in verge at the junction
A4-12	7301 (Non-Pres. Variant)	1050	750	0.78	n/a	RA2	2000	1	Steel circular section S275	76.1mm O.D. 4mm thick	3500	n/a	✓	1	600	900	1000	150	A	1200	in verge at the junction
A4-13	S13.9	1185	1885	2.23	100.00	RA2	2000	2	Steel circular section S275	88.9mm O.D. 5mm thick	4635	n/a	✓	1	600	1200	1500	150	B	1200	Approx. 150m in advance of junction
A4-14	7301 (Non-Pres. Variant)	1050	750	0.78	n/a	RA2	2000	1	Steel circular section S275	76.1mm O.D. 4mm thick	3500	n/a	✓	1	600	900	1000	150	A	1200	in verge at the junction
A4-15	7301 (Non-Pres. Variant)	1050	750	0.78	n/a	RA2	2000	1	Steel circular section S275	76.1mm O.D. 4mm thick	3500	n/a	✓	1	600	900	1000	150	A	1200	in verge at the junction
A4-16	2703	1435	600	0.86	100.00	RA2	2000	2	Steel circular section S275	76.1mm O.D. 3.2mm thick	3350	807	✓	1	600	1200	900	150	B	1200	in verge
A4-17	2703	860	360	0.31	60.00	RA2	2100	1	Steel circular section S275	76.1mm O.D. 3.2mm thick	3210	n/a	✓	1	600	700	700	150	A	back of footpath	Approx. 45m in advance of junction
A4-18	2703	860	360	0.31	60.00	RA2	2100	1	Steel circular section S275	76.1mm O.D. 3.2mm thick	3210	n/a	✓	1	600	700	700	150	A	back of verge	Approx.33m in advance of junction,place at back of verge behind the footpath
A4-19	2703	860	360	0.31	60.00	RA2	2100	1	Steel circular section S275	76.1mm O.D. 3.2mm thick	3210	n/a	✓	1	600	700	700	150	A	back of footpath	Approx.45m in advance of junction
A4-20	S13.9	950	540	0.51	60.00	RA2	2100	1	Steel circular section S275	76.1mm O.D. 3.2mm thick	3390	n/a	✓	1	600	800	800	150	A	back of footpath	Approx.55m in advance of junction

NETWORK RAIL (EAST WEST RAIL WESTERN SECTION PHASE 2)

NOTES:

- FOR DETAILS OF FOUNDATIONS PLEASE REFER TO DRAWING No. 133735\_RW\_EWR-XX-XX-DR-CH-000214.
- FOR DETAILS OF SIGN LOCATIONS PLEASE REFER TO DRAWING Nos. 133735\_RW\_EWR-XX-CC\_A4-DR-CH-010101 TO 010174.
- THE MINIMUM MOUNTING HEIGHT FOR SIGNS IS 1500mm, WHERE THERE IS A SLOPE POST LENGTHS HAVE **NOT** BEEN ADJUSTED ACCORDINGLY.
- INDIVIDUAL SIGN DESIGN ASSUMPTIONS AND ADDITIONAL RELEVANT INFORMATION IS SHOWN IN THE NOTES COLUMN.
- THE POSTS SHALL END 100mm FROM THE BASE OF FOUNDATION AND WHERE CHS OR RHS POSTS ARE USED THERE SHALL BE AN EARTH COVER OF 150mm.
- FINAL SIGN LOCATION TO BE APPROVED ON SITE BY CONTRACTOR IN ACCORDANCE WITH THE TRAFFIC SIGNS MANUALS.
- FOR DETAILS OF ALL PASSIVELY SAFE POSTS PLEASE REFER TO 1200 SERIES APPENDICES DOCUMENT No. 133735\_RW-EWR-XX-XX-SP-CH-001200.

Rev	Date	Description of Revisions	Dsmd	Chkd	Appr
B01	24/02/20	FOR INFORMATION		R.K.	S.H. S.A.
Status	SHARED - for Information				S2



Project  
East West Rail  
(Western Section)  
Phase 2

Drawing Title  
COMPOUND A4  
GREEN LANE  
CONSTRUCTION ACCESS ROUTE  
SIGNING SCHEDULE

Designed	Ravikumar KN	Signed	R. KN	Date	24/02/20
Drawn	Shiva Murthy	Signed	S. Murthy	Date	21/02/20
Checked	Sharon Hulme	Signed	S. Hulme	Date	24/02/20
Approved	Stephen Abe	Signed	S. Abe	Date	24/02/20

Scale(s)  
NTS  
ELR - Project Chainage (Miles Yards)  
XX -

Design Package Risk Classification  
Normal  
Sheet  
1 of 1

Alternative Reference  
Drawing Number  
133735\_RW-EWR-XX-CC\_A4-DR-CH-010175  
Revision  
B01

