
Sign ref.	TSRGD ref.	Sign face Mounting height					ounting beight	Supports					Foundation(s)					Foundation Type	Sethack		
		Width (mm)	Height (mm)	Area (m²)	X-Height (mm)	Material Class	class (mm)	No. Type	Post Diameter and Wall Thickness	Length (mm)	Post Centre	Illuminated	Passive safety	INO	epth mm)		/idth Length mm) (mm)		A or B	(mm)	Notes
A2-01	S13.9	1790	925	1.66	100.00	RA2	2000	1 Steel circular section S275	88.9mm O.D. 3mm thick	3275	n/a		✓	1	800	700	1300	150	А	2460	Approx. 135m downstream of junction
A2-02	2703	1675	1215	2.04	100.00	RA2	1500	1 Steel circular section S275	88.9mm O.D. 4mm thick	3565	n/a			1	800	800	1500	150	А	2250	Approx. 60m downstream of junction
A2-03	7301	1050	750	0.79	100.00	RA2	2000	1 n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	Α	280	At junction verge
A2-04	7301	1050	750	0.79	100.00	RA2	2000	1 n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	Α	1480	At junction Central Island
A2-05	7301	1050	750	0.79	100.00	RA2	2100	Sign to be mounted on telegraph pole							-	Mounted on Existing Telegraph Pole					
A2-06	7301	1050	750	0.79	100.00	RA2	2100	1 Steel circular section S275	76.1mm O.D. 3.2mm thick	3125	n/a		✓	1	800	700	900	150	Α	-	At junction verge
A2-07	2703	1970	1490	2.94	100.00	RA2	1500	1 Steel circular section S275	114.3mm O.D. 3.2mm thick	3840	n/a			1	800	800	1600	150	А	1200	Approx. 60m upstream of junction
A2-08	2703	1305	1475	1.92	100.00	RA2	2000	1 Steel circular section S275	88.9mm O.D. 4mm thick	3825	n/a			1	800	700	1500	150	А	2580	Approx. 120m upstream of junction
A2-09	2703	2060	1490	3.07	100.00	RA2	2000	2 Steel circular section S275	76.1mm O.D. 5mm thick	3840	1200			1	800	1600	1200	150	В	1200	Approx. 75m downstream of junction
A2-10	622.1A	1200	1200	1.13	100.00	RA2	2000	1 Steel circular section S275	76.1mm O.D. 3.2mm thick	3550	n/a			1	800	700	1100	150	А	1305	In Verge at Haul Road Crossing-2
A2-11	622.1A	1200	1200	1.13	100.00	RA2	2000	1 Steel circular section S275	76.1mm O.D. 3.2mm thick	3550	n/a			1	800	700	1100	150	А	Back of Verge	To be mounted back to back with 3B
3B	7011-60	1050	750	0.79	100.00	RA2	2000	For further Information please refer to drawing No. 133735_2A-EWR-OXD-XX-M2-CH-010250							Back of verge	To be mounted back to back A2-11					
A2-12	7306	1310	1500	1.97	100.00	RA2	2000	1 Steel circular section S275	88.9mm O.D. 4mm thick	3850	n/a			1	800	700	1500	150	А	1200	Approx. 75m downstream of Haul Road Crossing-2
A2-13	7305	1435	775	1.11	100.00	RA2	2000	1 Steel circular section S275	76.1mm O.D. 3.2mm thick	3125	n/a		✓	1	800	700	1100	150	А	1800	Approx. 10m upstream of Compound A2 Access
A2-14	7305	1385	575	0.80	100.00	RA2	2000	1 Steel circular section S275	76.1mm O.D. 3.2mm thick	2925	n/a		✓	1	800	700	900	150	А	1900	Placed in Verge opp. To Compound A2 Acess
A2-15	7301	1045	775	0.81	100.00	RA2	2000	1 Steel circular section S275	76.1mm O.D. 3.2mm thick	3125	n/a			1	800	700	900	150	А	Back of Verge	Approx. 236m towards south of track. Mounted back to back with sign 6
6	NP4-60	600	600	0.36	100.00	RA2	2000	For further Information please refer to drawing No. 133735_2A-EWR-OXD-XX-M2-CH-010250								Back of Verge	To be mounted back to back A2-15				
A2-16	7301	1045	775	0.81	100.00	RA2	2000	1 Steel circular section S275	76.1mm O.D. 3.2mm thick	3125	n/a			1	800	700	900	150	А	1700	Approx. 236m towards south of track

NETWORK RAIL (EAST WEST RAIL WESTERN SECTION PHASE 2)

NOTES:

- 1. FOR DETAILS OF FOUNDATIONS PLEASE REFER TO DRAWING No. 133735_RW_EWR-XX-XX-DR-CH-000214.
- 2. FOR DETAILS OF SIGN LOCATIONS PLEASE REFER TO DRAWING NoS.
- 133735_RW_EWR-XX-CC_A1-DR-CH-010101 TO 010119. & 133735_RW_EWR-XX-CC_A2-DR-CH-010101 TO 010139. 3. THE MINIMUM MOUNTING HEIGHT FOR SIGNS IS 1500mm,
- WHERE THERE IS A SLOPE POST LENGTHS HAVE **NOT** BEEN ADJUSTED ACCORDINGLY. 4. INDIVIDUAL SIGN DESIGN ASSUMPTIONS AND ADDITIONAL
- RELEVANT INFORMATION IS SHOWN IN THE NOTES COLUMN. 5. THE POSTS SHALL END 100mm FROM THE BASE OF
- FOUNDATION AND WHERE CHS OR RHS POSTS ARE USED THERE SHALL BE AN EARTH COVER OF 150mm. 6. FINAL SIGN LOCATION TO BE APPROVED ON SITE BY
- CONTRACTOR IN ACCORDANCE WITH THE TRAFFIC SIGNS MANUALS.
- 7. FOR DETAILS OF ALL PASSIVELY SAFE POSTS PLEASE REFER TO 1200 SERIES APPENDICES DOCUMENT No. 133735_RW-EWR-XX-XX-SP-CH-001200.





East West Rail (Western Section) Phase 2

COMPOUND A2 LAUNTON CONSTRUCTION ACCESS ROUTE SIGNING SCHEDULE

Designed	Ravikumar K	N	Signed	R. KN	Date 24/01/20					
Drawn	Beeresh M		Signed	B. M	Date 04/12/19					
Checked	Sharon Hulm	е	Signed	S. Hulme	Date 24/01/20					
Approved	Stephen Abe		Signed	S. Abe	Date 24/01/20					
Scale(s) 1:1000	1	ELR - Project Chainage (Miles Yards)								
Design Pac	kage Risk Classifi	ormal		She	4 4					
					1 of 1					

✓ APPROVED

Revision B01