

Sign ref.	TSRGD ref.	Sign face			X-Height (mm)	Material Class	Mounting height (mm)	No.	Supports					Foundation(s)				Foundation Type A or B	Minimum Setback (mm)	Notes		
		Width (mm)	Height (mm)	Area (m²)					Type	Post Diameter and Wall Thickness	Length (mm)	Post Centre	Illuminated	Passive safety	No.	Depth (mm)	Width (mm)				Length (mm)	Cover (mm)
B-MULTI-01	2706	1560	1520	2.30	75.00	RA2	2300	2	Steel circular section S275	114.3mm O.D. 3.2mm thick	4570	890			1	600	1300	1500	150	B	600	Approx. 5m upstream of existing lampost
B-MULTI-02	2706	1560	1520	2.30	75.00	RA2	1500	2	Steel circular section S275	88.9mm O.D. 5mm thick	3770	890			1	600	130	1300	150	B	600	Approx. 20m upstream of lane destination sign
B-MULTI-03	2703	1080	495	0.53	60.00	RA2	2300	1	Steel circular section S275	76.1mm O.D. 3.2mm thick	3545	n/a			1	600	600	1000	150	A	back of Verge	Placed at back of verge. Approx. 15m upstream of existing ADS
B-MULTI-04	2703	1080	495	0.53	60.00	RA2	1500	1	Steel circular section S275	76.1mm O.D. 3.2mm thick	2745	n/a	✓		1	600	600	1000	150	A	600	Approx. 5m upstream of existing lampost
B-MULTI-05	S13-9	2000	1075	2.15	100.00	RA2	1500	2	Steel circular section S275	76.1mm O.D. 5mm thick	3325	1174			1	600	1500	1200	150	B	1200	Approx. 150m upstream of junction
B-MULTI-06	2704	1830	825	1.51	100.00	RA2	3200*	2	Steel circular section S275	88.9mm O.D. 5mm thick	4775	1502			1	600	1900	1100	150	B	Rear of B3-01 and B3-02	Mounted back to back with B-MULTI-07, and high enough to unobscure existing signs
B-MULTI-07	2704	1830	825	1.51	100.00	RA2	3200*	n/a	n/a	n/a	n/a	n/a			n/a	n/a	n/a	n/a	n/a	n/a	n/a	Mounted back to back with B-MULTI-06, and high enough to unobscure existing signs

NOTES:

- FOR DETAILS OF FOUNDATIONS PLEASE REFER TO DRAWING No. 133735_RW-EWR-XX-CC-DR-CH-000214.
- FOR DETAILS OF SIGN LOCATIONS PLEASE REFER TO DRAWING No. 133735_RW-EWR-XX-CC_B3-DR-CH-010110 TO 010141
- THE MINIMUM MOUNTING HEIGHT FOR SIGNS IS 1500mm, WHERE THERE IS A SLOPE POST LENGTHS HAVE NOT BEEN ADJUSTED ACCORDINGLY.
- INDIVIDUAL SIGN DESIGN ASSUMPTIONS AND ADDITIONAL RELEVANT INFORMATION IS SHOWN IN THE NOTES COLUMN.
- THE POSTS SHALL END 100mm FROM THE BASE OF FOUNDATION AND WHERE CHS OR RHS POSTS ARE USED THERE SHALL BE AN EARTH COVER OF 150mm.
- FINAL SIGN LOCATION TO BE APPROVED ON SITE BY CONTRACTOR IN ACCORDANCE WITH THE TRAFFIC SIGNS MANUALS.

Rev	Date	Description of Revisions	Dsmd	Chkd	Appr	Submittal
B01	04/11/19	FOR INFORMATION		R.K.	S.H.	S.A.
Status	SHARED - for Information					S2



Project
**East West Rail
(Western Section)
Phase 2**

Drawing Title
**COMPOUNDS B1, B2, B3 AND A4
CONSTRUCTION ACCESS ROUTE
MULTIPLE SIGNING SCHEDULE
SHEET 2 OF 2**

Designed	Ravikumar KN	Signed	R. KN	Date	31/10/19
Drawn	Sharon Hulme	Signed	S. Hulme	Date	27/09/19
Checked	Sharon Hulme	Signed	S. Hulme	Date	31/10/19
Approved	Stephen Abe	Signed	S. Abe	Date	31/10/19

Scale(s)	1:1000	ELR - Project Chainage (Miles/Yards)	XX -
Design Package Risk Classification	Normal	Sheet	2 of 2
Alternative Reference		Revision	B01
Drawing Number	133735_RW-EWR-XX-CC_B3-DR-CH-010143		

