

FLOOD MODELLING REPORT

# Firethorn Developments Limited

Land at North West Bicester

February 2021

## Contents

1	Introduction .....	1
2	Consultation .....	4
3	Flood Model Development.....	5
4	Model Results .....	12
5	Sensitivity Testing .....	16
6	Conclusion.....	24

## Appendices

Appendix 1	– Environment Agency Correspondence
Appendix 2	– Hydrological Analysis
Appendix 3	– Watercourse Survey
Appendix 4	– Flood Maps

# 1 Introduction


## Authorisation

1.1 This flood modelling study has been undertaken by Vectos on behalf of Firethorn Developments Limited. This has been undertaken to support the outline planning application (21/01630/OUT) at North West Bicester.

## Background

1.2 Town Brook, an ordinary watercourse, flows alongside the east boundary of the site. A tributary of Town Brook, another ordinary watercourse, flows alongside the south boundary of the site (these are further described in Section 3).


1.3 The Environment Agency Flood Map for Planning (available from <https://flood-map-for-planning.service.gov.uk/>) identifies the fluvial flood extents across the site associated with Town Brook. These are presented in Figure 1, which shows that Town Brook results in some relatively limited flooding alongside the east site boundary.



**Figure 1: Flood Zone 3 and Flood Zone 2**

1.4 Typically, the Flood Map for Planning excludes watercourses with catchment areas less than 3 km<sup>2</sup>. This includes the tributary on the south site boundary. However, flooding associated with this tributary is presented on the Risk of Flooding from Surface Water map. These surface water flood

zones are presented in Figure 2. Similar to Town Brook, some relatively limited flooding is identified alongside the site boundary.



**Figure 2: Surface Water Flood Zones**

- 1.5 In the proximity of the site, the Flood Map for Planning has been derived using JFLOW. This is a broad-brush flood modelling technique, which was developed as part of the national flood mapping programme. The methodology takes little or no account of watercourse capacity, nor does it allow for hydraulic structures, and is often found to result in an overestimation of flooding. A similar approach was adopted for the Risk of Flooding from Surface Water map and the accuracy of the associated flood mapping can be poor.
- 1.6 The Flood Risk Assessment (FRA) prepared to support the planning application at the site considered these sources of flood risk and made allowances for climate change. However, following their review of the FRA, the Environment Agency (EA) stipulated the need for hydraulic modelling to obtain a more reliable estimation of flood risk, which should be used for comparison to development proposals.

**Purpose of this Report**

- 1.7 The purpose of this report is to summarise details of the flood modelling undertaken. The flood modelling objectives were defined at the outset of this study, these were:
  - i) Derive hydrological boundaries (i.e. design inflows) for the study area;

- ii) Develop a baseline 1D-2D hydraulic model of the site, extending both up and downstream;
  - iii) Simulate the hydraulic model for a series of design inflow events;
  - iv) Derive baseline flood maps for the site for comparison to the existing flood zones, Land Use Parameters Plans, Framework Plan and Illustrative Masterplan.
- 1.8 The work has been undertaken in accordance with the guidelines set out in the National Planning Policy Framework (NPPF).

## **2 Consultation**

- 2.1 A modelling methodology was prepared and issued to the EA for comment. The EA response was used to inform the preparation of the flood model. Details are enclosed in Appendix A.

### 3 Flood Model Development


3.1 The flood model has been developed to improve the understanding of fluvial flood risk at the site. The flood model comprises of two parts: the hydrological model and the hydraulic model. Both of which are discussed in this section.

#### Hydrological Modelling

3.2 The hydrological assessment allows for the calculation of watercourse flows, or design hydrographs, which are subsequently used as inflow boundary conditions in the hydraulic model.

3.3 The hydrographs were estimated using the latest methodologies described in the Flood Estimation Handbook (FEH). Ultimately, the statistical method has been selected to derive design hydrographs at the site due to the permeable nature of the catchment. This method was found to result in slightly lower peak flows than the ReFH (2.2) method.

3.4 Design hydrographs have been derived to represent three separate runoff contributions. These relate to two upstream catchment areas and from within the model reach itself (i.e. applied as lateral inflows). Figure 3 shows the extents of the contributing areas for which design hydrographs have been derived.



**Figure 3: Hydrological Areas**

3.5 Table 1 presents a summary of the peak flows associated with each design event, for the total catchment area. It also includes the size of each catchment, which has been used to scale the peak flows. These scaled peak flows are also identified. The lateral peak flows were estimated by

deducting the peak flows associated with the two upstream catchment areas (i.e. R01 and R02) from the total catchment peak flow.

**Table 1: Estimated Peak Flows (m<sup>3</sup>/s)**

Design Event	Catchment			
	Total	Reach 1	Reach 2	Lateral
	7.60 km <sup>2</sup>	3.88 km <sup>2</sup>	0.53 km <sup>2</sup>	3.19 km <sup>2</sup>
1 in 20	0.64	0.33	0.04	0.27
1 in 100	0.98	0.50	0.07	0.41
1 in 100 + 15%CC	1.13	0.58	0.08	0.47
1 in 100 + 25%CC	1.23	0.63	0.09	0.51
1 in 1000	1.74	0.89	0.12	0.73

3.6 A hydrograph shape was obtained from the ReFH2 method and applied to all inflows.

3.7 Full details of the hydrological analysis are outlined in Appendix B.

### Baseline Hydraulic Modelling

3.8 The baseline hydraulic model has been developed using TUFLOW software. TUFLOW is an industry standard computational engine that provides one-dimensional (1D) and two-dimensional (2D) solutions of the free-surface flow equations to simulate hydrodynamic behaviour in river, floodplains and urban drainage environments. The 1D component uses a tool built into TUFLOW, called ESTRY. The TUFLOW software version used was 2020-10-AA-iDP-w64.

3.9 General details concerning the hydraulic model development, parameters and assumptions are outlined in the following sections.

### Hydraulic Model Approach and Extent

3.10 A linked 1D-2D model has been developed including the entire extent of the existing flood zones on site. It has also extended 600 m upstream and 800 m downstream of the site. A 1D model of the stream network and hydraulic structures has been incorporated to accurately represent in channel hydraulics, with this linked to a 2D floodplain domain.

3.11 The 1D model extends across the full length of the 2D model. The downstream extent was chosen because it was located sufficiently far from the site in order to minimise boundary effects.

3.12 Figure 4 illustrates the extent of the 1D and 2D model.

### Model Grid Size

3.13 The model was constructed with a 2 m grid cell size. This was chosen as it represented a good balance between the degree of precision (i.e. ability to model overland flow paths along roads or through ditches) and model run (“simulation”) times.



## Topographic Data

- 3.14 1 m resolution LiDAR (Light Detection And Ranging) data, which was captured in 2020, was downloaded to provide a Digital Terrain Map (DTM) of the study area including the site and surrounding catchment. This covered the entire 2D model extent and was used to represent floodplain ground levels.



**Figure 4: 1D and 2D Model Extent**

- 3.15 The site topographic survey was used to validate the LiDAR data. The two data sets were found to compare well across the site. Consequently, the LiDAR was considered to be acceptable for use as part of the hydraulic model.
- 3.16 A cross section topographic survey of the watercourse and hydraulic structures was captured across the full length of the 1D model. Details are enclosed in Appendix C.

## Upstream Boundary Conditions

- 3.17 The hydrographs derived as part of the hydrological modelling were incorporated into the hydraulic model as upstream boundary conditions (i.e. inflows). The two upstream catchments were incorporated into the most upstream 1D cross section / node, for Reach 1 and Reach 2. The lateral inflows were proportioned across the model reach (see Figure 5).

### Downstream Boundaries

- 3.18 A stage-discharge boundary was added to allow water to exit the 2D model at the downstream extent. The stage-discharge relationship is calculated automatically by TUFLOW based on gradients determined from LiDAR data.
- 3.19 A fixed water level of 78.14 m AOD was applied as a downstream boundary for the 1D model. This was the surveyed water level and is thought to represent a typical likely dry weather flow condition. Alternative, more conservative, methods for a downstream boundary condition were tested but introduced instability into the model during model testing.



**Figure 5: Inflow Locations**

- 3.20 The results in the proximity of the site were not considered to be sensitive to this boundary condition given the distance and level differences. However, the sensitivity of the model to this downstream boundary conditions was tested and is discussed in Section 5 of this report.

### Structures

- 3.21 The watercourse survey captured a total of 21 structures, which are summarised in Table 2. All surveyed structures were included in the hydraulic model. Figure 6 presents the location of these various structures.
- 3.22 On Reach 1 a lake is present upstream of the B4100 (see Figure 7). Water flows both in and out of the lake at the same location (at node 01450). However, an overflow is present at the downstream

extent of the lake, which flows in a culvert beneath the B4100. The water level in the lake was set to be full (i.e. 85.04 m AOD, which is equivalent to the invert level of the culvert that provides flow into it).

- 3.23 The only surveyed feature that was ignored is a small pond located at the upstream extent of Reach 2. The modelled watercourse supplies flow to this pond, but its inclusion was thought to offer no benefit to the accuracy of the model results. In theory it could offer some storage potential, so its exclusion was conservative.



**Figure 6: Structure Locations**

**Floodplain Topography**

- 3.24 The only change to the floodplain topography was the inclusion of a stone wall that surrounds the lake. A gap in this wall was included, at the location of a small gate.

**Hydraulic Roughness**

- 3.25 Hydraulic roughness is the measure of the amount of frictional resistance water experiences when passing over land and channel features. Manning’s ‘n’ coefficient values provide a measure of these roughness values. The river channel and floodplain were assigned a roughness value with reference to standard values (Chow, 1959).

- 3.26 Roughness values are variable and include a default value of 0.06 for arable land and 0.02 for roads, for example. Limited variation in Manning’s values was noted across the small rural model extent.

3.27 Roughness land uses were defined using aerial photography, which was considered adequate given the rural floodplain and small variation in land use.



**Figure 7: Lake and Wall Locations**



**Figure 8: Wall Surrounding the Lake**

- 3.28 A relatively high Manning's value of 0.06 was adopted for the 1D river channel. This was because a reasonable amount of vegetation was noted to creep into the channel during summer months. Therefore, a conservative approach was adopted to represent these summer conditions.

### **Linking**

- 3.29 The 2D model was dynamically linked to the 1D model using a 'HX' boundary, which transfers flows based on a water level between the two models.

### **Model Run Parameters**

- 3.30 The default TUFLOW Classic model run parameters were used and adopted for all simulations.

### **Design Runs**

- 3.31 The baseline and proposed hydraulic models were simulated for the following design events:
- i) 1 in 20 year event.
  - ii) 1 in 100 year event.
  - iii) 1 in 100 year event plus a 15% allowance for climate change event (central estimate).
  - iv) 1 in 100 year event plus a 25% allowance for climate change event (higher central estimate).
  - v) 1 in 1000 year event.
- 3.32 These climate change allowances are in accordance with latest Planning Practice Guidance, which indicates that the central estimate (i.e. 15%) is applicable for the site. It is this 1 in 100 year event plus a 15% allowance for climate change event that represents the key design event which development must be protected from.
- 3.33 Based on the recommended ranges for the cell size, a 0.5 second timestep was adopted for the 2D TUFLOW model. A 0.25 second timestep was adopted for the 1D component.

## 4 Model Results

### Model Stability

- 4.1 The stability of a model is critical to the understanding of the robustness and its ability to simulate a flood event accurately.
- 4.2 Stability in the model is assessed by examining the cumulative error (or mass balance) of the model, as well as the warnings output by the model during the simulation.
- 4.3 The 1 in 100 year plus 15% climate change event was run using TUFLOW Classic. Iterations of the model were undertaken to improve stability etc, where necessary. The cumulative error of the model is within the range of  $\pm 1.3\%$  throughout the simulation. No negative depths were encountered. Various warnings and checks occurred prior to the simulation, which were found to be of little consequence and were therefore considered acceptable.
- 4.4 Similar observations were made for the wider design simulations.

### Baseline Model Results

- 4.5 The results have been summarised through the presentation of a flood map showing the various design events. This is shown in Figure 9. Further flood mapping is enclosed in Appendix D.
- 4.6 It can be seen that in a 1 in 20 year event, flooding is limited to the confluence of the two streams. However, in a 1 in 100 year event, flooding on the east site boundary occurs. This is a result of the capacity restriction associated with a series of hydraulic structures downstream of the B4100. Under the model extreme events, the flood extents become broader but limited other areas experience flooding. It is noted that floodwater is contained within the banks of Reach 2. The downstream reach of the model first floods in a 1 in 1000 year event.
- 4.7 The 1 in 1000 year flood event generates the most extensive floodplain out of the various design events investigated. Figure 10 compares this with the flood extent on the Flood Map for Planning (i.e. Flood Zone 2). It shows that the flood extents derived from this study are smaller than that presented on the Flood Map for Planning. They are also smaller than the flood extents presented on the Risk of Flooding from Surface Water Map (Figure 12).
- 4.8 As part of the FRA prepared to support the planning application, a climate change flood extent was derived based on the extrapolation of JFLOW flood levels. The resultant flood extent is shown in Figure 13. This extrapolated flood extent, along with the flood extents presented on the Flood Map for Planning and Risk of Flooding from Surface Water Map, were all originally used to inform the Land Use Parameters Plans, Framework Plan and Illustrative Masterplan associated with the planning submission. This ensured that the proposed development (including SuDS) was entirely steered out of the floodplain.
- 4.9 The flood extents prepared as part of this flood modelling study are no greater than those extents previously available and it can be concluded therefore, that the development remains safe from flooding without impacting on third parties. This is therefore in accordance with the requirements of planning policy.



Figure 9: All Flood Extents



Figure 10: Comparison of Modelled 1 in 1000 Year Event and Flood Zone 2




Figure 11: Comparison of Modelled 1 in 100 Year Event and Flood Zone 3



Figure 12: Comparison of Modelled 1 in 1000 Year Event and Surface Water Flood Extent





**Figure 13: Comparison of Modelled 1 in 1000 Year Event and FRA Extrapolated Flood Zone**

**Model Uncertainty**

- 4.10 The catchment upstream of the site is ungauged and permeable. Therefore, some uncertainty exists with respect to the accuracy of the hydrological and hydraulic model. The results presented are the best available, within the confines of available information.

## 5 Sensitivity Testing

5.1 Sensitivity testing is the process of adjusting key parameters within the hydraulic model to examine the impact. This allows an understanding of how any uncertainty associated with those parameters may affect the outcome of the model. Sensitivity testing is often undertaken in the absence of data used for the calibration purposes. Sensitivity testing has been undertaken on the following parameters:

- i) Manning’s ‘n’ roughness;
- ii) Flow;
- iii) Downstream boundary condition; and
- iv) Blockages.


5.2 The sensitivity testing has been undertaken on the basis of the 1 in 100 year event.

### Manning’s ‘n’ Roughness

5.3 Manning’s ‘n’ roughness was adjusted by  $\pm 20\%$  in the channel and floodplain. The results of this sensitivity test are identified in Figure 14 and 15, which are difference maps compared to the baseline model.



**Figure 14: Manning’s Plus 20% Difference Map**



**Figure 15: Manning’s Minus 20% Difference Map**

5.4 The results of the sensitivity testing show a similar impact in both the decreased and increased scenarios. The variation in peak water level is minor for what is a relatively significant adjustment to roughness values. The model is therefore not considered to be particularly sensitive to Manning’s roughness.

**Flow**

5.5 The upstream boundary condition (i.e. inflow) was adjusted by  $\pm 20\%$ . The results of this sensitivity test are identified in Figure 16 and 17, which are difference maps compared to the baseline model.


5.6 The results of the sensitivity testing show a similar impact in both the decreased and increased scenarios. The variation in peak water level is minor for what is a relatively significant adjustment to inflow values. The model is therefore not considered to be particularly sensitive to inflows.

**Downstream Boundary Conditions**

5.7 The downstream boundary condition was modified by applying an elevated water level throughout the simulation in both 1D and 2D. This was increased from 78.14 m AOD to 79.5 m AOD. A level of 79.5 m AOD was determined based on the estimated flood level for the 1 in 1000 year event from the Flood Map for Planning. It meant that the culvert on the downstream boundary was submerged throughout the simulation in the sensitivity test. The results of this sensitivity test are identified in Figure 18, which is a difference map compared to the baseline model.



**Figure 16: Flow Plus 20% Difference Map**



**Figure 17: Flow Minus 20% Difference Map**



**Figure 18: Increased Downstream Boundary Difference Map**

5.8 The impacts are significant at the downstream end of the hydraulic model, but with distance upstream from the downstream boundary, the effects become less significant. The effects of the downstream boundary were not felt at the site. This is important because it confirms that any uncertainty associated with the downstream boundary is likely to have no effect upon peak water levels at the site.

### Summary

5.9 Generally, the watercourse was found to be relatively insensitive to adjustments of key parameters within the hydraulic model. Consequently, the model is considered to offer a robust representation of the watercourse for this assessment and peak water levels/flood extents are considered reliable.

### Blockages

5.10 Whilst not required by the EA, as part of their model methodology review, the impact of blockages was also assessed. Following a site visit it was considered that the hydraulic structures most likely to increase flooding on site were beneath the B4100.

5.11 If these were to block, water would accumulate upstream in the proximity of the lake and spill towards the site once flood levels get high enough to flow through the gap/gate in the wall. As part of this blockage assessment, the lake was set to be full (i.e. above culvert inlet / outlet level and up to bank top). This conservative approach was not possible under a non-blocked scenario, because

water drains out of the lake into the stream at the start of the simulation. To achieve this, the culvert inlet / outlet was modelled as 100% blocked.

5.12 As series of very conservative blockage scenarios have been assessed, which are as described below:

1. Main culvert beneath B4100 100% blocked, lake full – see Figure 19
2. All culverts beneath B4100 100% blocked, lake full – see Figure 20
3. All culverts on site 100% blocked, lake not full – see Figure 21



**Figure 19: Blockage Scenario 1**

5.13 The flood depth results are presented in Figure 22 to 24. Ultimately, whilst different flood mechanisms are identified as a result of the three blockage scenarios the flood extents on site are no greater than that identified in the 1 in 1000 year event. Therefore, the conclusions drawn in Section 4 are still valid.



Figure 20: Blockage Scenario 2



Figure 21: Blockage Scenario 3



Figure 22: Flood Depth Map – Blockage Scenario 1



Figure 23: Flood Depth Map – Blockage Scenario 2





**Figure 24: Flood Depth Map – Blockage Scenario 3**

## 6 Conclusion

- 6.1 This flood modelling study has been undertaken by Vectos on behalf of Firethorn Developments Limited. This has been undertaken to support the outline planning application (21/01630/OUT) at North West Bicester.
- 6.2 Following the EA review of the planning submission, they stipulated the need for hydraulic modelling to obtain a reliable estimation of flood risk, which should be used for comparison to development proposals.
- 6.3 The flood modelling study has been completed using 1D-2D ESTRY-TUFLOW software to investigate the fluvial flood risk associated with two ordinary watercourses on the site boundary. This has shown that the existing Flood Map for Planning and Risk of Flooding from Surface Water map overestimate the floodplain in the proximity of the site.
- 6.4 Given that the Land Use Parameters Plans, Framework Plan and Illustrative Masterplan for the proposed development were all based on these desktop sources of flood risk, it can be concluded that the development remains safe from flooding without impacting on third parties.

# Appendix 1

Environment Agency Correspondence

Mr Nick Bosanko  
Vectos  
4 Colston Avenue  
Bristol  
Avon  
BS1 4ST

**Our ref:** WA/2021/129288/01-L01  
**Agreement No:** ENVPAC/1/THM/00590  
**Your ref:** 21/01630/OUT  
**Date:** 04 October 2021

Dear Mr Bosanko

### **Planning advice for North West Bicester**

Thank you for accepting our offer to provide detailed planning advice. The advice detailed below is intended to inform your development proposal. It is not our statutory response to a planning application consultation.

We are providing this advice under Agreement No. ENVPAC/1/THM/00590 and Firethorn Developments will be invoiced accordingly.

We have reviewed the proposed modelling methodology you submitted by email dated 22/07/2021.

**Please note** that we are only providing you with our advice on the matters as outlined in our offer as requested.

### **Hydrology**

The proposed hydrological analysis will be performed using ReFH2 and statistical techniques for all key design storms. This is an appropriate approach. The return periods of 5%, 1%, 1% CC and 0.1% AEP are appropriate, although further return periods such as 10%, 2% and 0.5%AEP should be considered. The climate change uplift is noted as 35% for the Thames higher central estimate. A further climate change simulation with an upper end estimate is suggested. Any climate change uplifts should follow appropriate climate change guidance.

A sensitivity test should be completed with flow + /- 20% for the 1% AEP return period.

The location for the hydrological analysis is appropriate.

### **Hydraulics**

Did you know the Environment Agency has a **Planning Advice Service**? We can help you with all your planning questions, including overcoming our objections. If you would like our help please email us at [planning\\_THM@environment-agency.gov.uk](mailto:planning_THM@environment-agency.gov.uk)

A 1D-2D model is appropriate for this study, with the 1D-2D links using HX boundaries. The 2D model extent matches the proposed 1D so the whole model will be 1D in-channel and 2D floodplain. A 2m cell size using 1m LiDAR is appropriate and should give good resolution of the model without heavily compromising run times.

The survey coverage is appropriate and appears to contain all future intended structures across the river channels. Any further alterations to the site plans around the channel should be incorporated into the model.

The 2D Manning's roughness is suggested as 0.05 for agricultural fields and aerial photography will be used to define other roughness values. Whilst this is appropriate it is suggested that mastermap data is used to define the roughness values on the floodplain, with updates to the roughness used for the design/with scheme simulation.

The downstream boundary location appears to be appropriate. Vectos describes the initial backwater calculation showing an appropriate distance downstream of the site. Results at this location should be investigated following to ensure that there is no flow or stage increase in the design/with scheme simulations. Any increase will require further investigation and possibly the requirement to map the knock-on effects downstream of the proposed model.

Sensitivity tests have not been included within the methodology proposal. These should be undertaken with + /-20% sensitivities to the inflows, manning's n and downstream boundary.

The modelling will be required to follow Environment Agency guidance which you can access through the following link:

<https://www.gov.uk/government/publications/river-modelling-technical-standards-and-assessment>

### **Conclusions**

The modelling methodology is reasonable for the study. As mentioned above further considerations should be taken for inflows and sensitivity tests and particular attention should be given to the downstream boundary, although the methodology supplied suggests initial tests suggest it is appropriate.

### **Next steps**

Any modelling compiled in support of the development at North West Bicester will need to undergo a technical review by the Environment Agency. Please note that a review can take anywhere between 3 – 8 weeks depending on the nature of the model and programme of reviews already underway.

### **Final comments**

Once again, thank you for contacting us with your enquiry. Our comments are based on our available records and the information as submitted to us.

I hope the above advice is helpful. If there is any further work you anticipate needing our detailed advice on in relation to this project, please let me know so it can be incorporated into this charging agreement.

### **Disclaimer**

Please note that the views expressed in this report by the Environment Agency, is a response to a pre-application enquiry only and **does not represent our final view in**

**relation to any future statutory consultations made in relation to this site.** We reserve the right to change our position in relation to any such application.

We have only provided advice in relation to the environmental constraints as outlined in our offer as requested. However, we will comment on all environmental constraints within our remit in our statutory response.

Please quote our reference number in any future correspondence. If you have any queries please feel free to contact me.

Yours sincerely

**Miss Sarah Green**  
**Sustainable Places - Planning Advisor**

Direct dial 0208 474 9253

Direct e-mail [planning\\_THM@environment-agency.gov.uk](mailto:planning_THM@environment-agency.gov.uk)

## Appendix 2

Hydrological Analysis

(See digital version for all details)

# Flood estimation report: Land at Northwest Bicester

## Introduction

This report template is a supporting document to the Environment Agency's Flood Estimation Guidelines. It provides a record of the hydrological context, the method statement, the calculations and decisions made during flood estimation and the results.

## Contents

1	<b>SUMMARY OF ASSESSMENT</b> .....	1
2	<b>METHOD STATEMENT</b> .....	2
3	<b>LOCATIONS WHERE FLOOD ESTIMATES REQUIRED</b> .....	4
4	<b>STATISTICAL METHOD</b> .....	5
6	<b>REVITALISED FLOOD HYDROGRAPH 2 (REFH2) METHOD</b> .....	7
7	<b>DISCUSSION AND SUMMARY OF RESULTS</b> .....	8

## Approvals

Revision stage	Analyst / Reviewer name & qualifications	Amendments	Date
Method statement preparation	GEORGE FRISBY	N/A	02/11/2021
Initial calculations preparation	GEORGE FRISBY	N/A	02/11/2021
Calculations - Revision 1 preparation	GEORGE FRISBY	N/A	02/11/2021
Report Update in Response to EA Comments	GEORGE FRISBY		04/02/2022

*Review by Matthew Scott*



## Abbreviations

AEP	.....	annual exceedance probability
AM	.....	Annual Maximum
AREA	.....	Catchment area (km <sup>2</sup> )
BFI	.....	Base Flow Index
BFIHOST	.....	Base Flow Index derived using the HOST soil classification
CPRE	.....	Council for the Protection of Rural England
FARL	.....	FEH index of flood attenuation due to reservoirs and lakes
FEH	.....	Flood Estimation Handbook
FSR	.....	Flood Studies Report
HOST	.....	Hydrology of Soil Types
NRFA	.....	National River Flow Archive
OS	.....	Ordnance Survey
POT	.....	Peaks Over a Threshold
QMED	.....	Median Annual Flood (with return period 2 years)
ReFH	.....	Revitalised Flood Hydrograph method
ReFH2	.....	Revitalised Flood Hydrograph 2 method
SAAR	.....	Standard Average Annual Rainfall (mm)
SPR	.....	Standard percentage runoff
SPRHOST	.....	Standard percentage runoff derived using the HOST soil classification
Tp(0)	.....	Time to peak of the instantaneous unit hydrograph
URBAN	.....	Flood Studies Report index of fractional urban extent
URBEXT1990	.....	FEH index of fractional urban extent
URBEXT2000	.....	Revised index of urban extent, measured differently from URBEXT1990
WINFAP-FEH	.....	Windows Frequency Analysis Package – used for FEH statistical method

# 1 SUMMARY OF ASSESSMENT

## 1.1 Summary

This table provides a summary of the key information contained within the detailed assessment in the following sections. The aim of the table is to enable quick and easy identification of the type of assessment undertaken. This should assist in identifying an appropriate reviewer and the ability to compare different studies more easily.

Catchment location	North Bicester - 457650,224300
Purpose of study and scope	Inflows for hydraulic model – A lumped catchment (DS_R01) and two sub catchments (US_R01 and US_R02).
Key catchment features	Permeable Catchment – Rural
Flooding mechanisms	Fluvial and potential Groundwater
Gauged / ungauged	Ungauged
Final choice of method	FEH
Key limitations / uncertainties in results	Interaction with Groundwater during long duration storm events.

## 1.2 Note on flood frequencies

The frequency of a flood can be quoted in terms of a return period, which is defined as the average time between years with at least one larger flood, or as an annual exceedance probability (AEP), which is the inverse of the return period.

Return periods are output by the Flood Estimation Handbook (FEH) software and can be expressed more succinctly than AEP. However, AEP can be helpful when presenting results to members of the public who may associate the concept of return period with a regular occurrence rather than an average recurrence interval. Results tables in this document contain both return period and AEP titles; both rows can be retained or the relevant row can be retained and the other removed, depending on the requirement of the study.

The table below is provided to enable quick conversion between return periods and annual exceedance probabilities.

**Annual exceedance probability (AEP) and related return period reference table**


<b>AEP (%)</b>	50	20	10	5	3.33	2	1.33	1	0.5	0.1
<b>AEP</b>	0.5	0.2	0.1	0.05	0.033	0.02	0.0133	0.01	0.005	0.001
<b>Return period (yrs)</b>	2	5	10	20	30	50	75	100	200	1,000

## 2 METHOD STATEMENT

### 2.1 Requirements for flood estimates

Overview	<p>Estimate peak flows and generate associated hydrographs for use as upstream boundary conditions/inflows to a hydraulic model covering Bainton, Swallowfield Farm and Caversfield.</p> <p>1 lumped catchment and 2 sub catchments.</p> <p>0.05, 0.01 and 0.001 AEP flood events Allowance for climate change (CC) of 15 and 25% (allowance for relevant EA catchment) applied to the 0.01 AEP hydrographs in the hydraulic model.</p>
Project scope	No existing hydrological studies incorporated into this assessment.

### 2.2 The catchment



Description	<p>The total area is divided into one lumped catchment and 2 sub catchments as shown in the figure above. The two main catchment watercourses converge at 457882, 224889 before flowing south west – under the A4095 Bicester bypass, which forms the lumped catchment (DS_R01) outlet.</p> <p>The Geology of the catchment is predominantly Cornbrash Formation Limestone, with in channel bedrock of Forest Marble Limestone and Mudstone and superficial deposits of alluvium (clay, silt, sand and gravel). The porous limestone in the catchment leads to high levels of permeability.</p> <p>Rural, predominantly agricultural catchment area with low relief, falling from approx. 120m Above Ordnance Datum in the northern upper end of the catchment, to 80m AOD at the Bicester bypass and catchment outlet.</p>
-------------	---

## 2.3 Source of flood peak data

Source	NRFA peak flows dataset, Version 10, released August 2020/21. This contains data up to water year 2019/20.
--------	--

## 2.4 Gauging stations (flow or level)

All Gauging stations below are deemed suitable for QMED estimates

Water-course	Station name	NRFA number	Distance (km)	BFIHOST	Catchment area (km <sup>2</sup> )	QMED observed	Pooling Suitability
Bedford	Thornborough Mill	33005	11.34	0.822	387.67	21.8	Yes
Cherwell	Enslow Mill	39021	17.72	0.48	555.45	19.3	Yes
Tove	Cappenham Bridge	33018	22.39	0.59	132.55	17.04	No
Cherwell	Banbury	39026	24.7	0.368	204.59	16.731	No
<b>Evenlode</b>	<b>Cassington Mill</b>	<b>39034</b>	<b>24.86</b>	<b>0.41</b>	<b>427.14</b>	<b>20.6</b>	<b>Yes</b>
Thames	Days Weir	39002	29.63	0.699	3480.00	148.014	Yes

## 2.5 Hydrological understanding of catchment

Conceptual model	Main site of interest is at Caversfield House, and therefore flood risk is dominated by flows in US_R01. Therefore, the critical duration for this reach will dictate the durations for the other catchments.
Unusual catchment features	FEH catchment descriptors indicate the catchment is highly permeable – with very high BFIHOST of 0.822 and a low SPRHOST of 15.59%.

## 2.6 Initial choice of approach

Is FEH appropriate?	Yes
Initial choice of method(s) and reasons How will hydrograph shapes be derived if needed? Will the catchment be split into sub-catchments? If so, how?	FEH statistical method – Including permeable adjustment method as the SPRHOST of the catchment is below the threshold of 20%.  Hydrographs will be derived using ReFH2.  FEH statistical method will be completed on the total lumped catchment (DS_R01). ReFH2 completed on the lumped catchment and the sub catchments. US_R01 and US_R02 sub catchment hydrographs to be scaled proportionately using the FEH static method and the relative peak flows derived from the ReFH2 hydrographs.
Software to be used (with version numbers)	FEH Web Service <sup>1</sup> / WINFAP 42.7282 <sup>2</sup> / ReFH spreadsheet / ReFH2.3 / Flood Modeller Pro

<sup>1</sup> CEH 2015. The Flood Estimation Handbook (FEH) Online Service, Centre for Ecology & Hydrology, Wallingford, UK.

<sup>2</sup> WINFAP 4 © Wallingford HydroSolutions Limited 2016.

### 3 LOCATIONS WHERE FLOOD ESTIMATES REQUIRED

The table below lists the locations of subject sites. The site codes listed below are used in all subsequent tables to save space.

#### 3.1 Summary of subject sites and key catchment descriptors

Site code	Type of estimate L: lumped catchment S: Sub-catchment	Watercourse (all officially unnamed)	Easting	Northing	AREA on FEH Webservice	BFI HOST	SPR HOST (%)	URBEXT 2000	FARL
DS_R01	L	Reach 1	457650	224300	7.60	0.822	15.59	0.0105	0.965
US_R01	S	Reach 1	458100	225550	3.88	0.788	18.08	0.0071	1
US_R02	S	Reach 2	456700	225700	0.53	0.754	20.58	0.0165	1

Note: Lumped catchments (L) are complete catchments draining to points at which design flows are required.  
 Sub-catchments (S) are catchments or intervening areas that are being used as inputs to a semi-distributed model of the river system. There is no need to report any design flows for sub-catchments, as they are not relevant: the relevant result is the hydrograph that the sub-catchment is expected to contribute to a design flood event at a point further downstream in the river system. This will be recorded within the hydraulic model output files. However, catchment descriptors and ReFH model parameters should be recorded for sub-catchments so that the results can be reproduced.  
 The schematic diagram illustrates the distinction between lumped and sub-catchment estimates.

#### 3.2 Checking catchment descriptors

Record how catchment boundary was checked and describe any changes	The FEH webservice catchment delineation was checked against OS mapping contours and contoured 2m LiDAR data and was found to be an appropriate estimate for the catchment.
Record how other catchment descriptors were checked and describe any changes.	Checked against OS mapping and BGS superficial/bedrock geology and hydrogeology maps. High permeability values were validated due to the predominant limestone geology of the area.

## 4 STATISTICAL METHOD

### 4.1 Application of Statistical method

What is the purpose of applying this method?	Statistical method applied only for the overall lumped catchment (DS_R01). This is the only catchment deemed appropriate for this type of analysis – with the subcatchments being too small (less than 5km <sup>2</sup> )
--	---

### 4.2 Overview of estimation of QMED at each subject site

Site code	QMED (rural) from CDs (m <sup>3</sup> /s)	Final method	Data transfer					Urban adjustment factor UAF	Final estimate of QMED (m <sup>3</sup> /s)
			NRFA numbers for donor sites used (see 4.3)	Distance between centroids d <sub>ij</sub> (km)	Moderated QMED adjustment factor, (A/B) <sup>a</sup>	If more than one donor			
						Weight	Weighted ave. adjustment		
DS_01	0.290	0.298	1	24.86		1	-	-	<b>0.298</b>
Are the values of QMED spatially consistent?						-			
Method used for urban adjustment for subject and donor sites						WINFAP v4 <sup>3</sup>			
<b>Parameters used for WINFAP v4 urban adjustment if applicable</b>									
Impervious fraction for built-up areas, IF			Percentage runoff for impervious surfaces, PR <sub>imp</sub>			Method for calculating fractional urban cover, URBAN			
0.3			70%			From updated URBEXT2000			
<b>Notes</b>									
Methods: AM – Annual maxima; POT – Peaks over threshold; DT – Data transfer (with urban adjustment); CD – Catchment descriptors alone (with urban adjustment); BCW – Catchment descriptors and bankfull channel width (add details); LF – Low flow statistics (add details).									
The QMED adjustment factor A/B for each donor site is moderated using the power term, a, which is a function of the distance between the centroids of the subject catchment and the donor catchment. The final estimate of QMED is (A/B) <sup>a</sup> times the initial (rural) estimate from catchment descriptors.									
<b>Important note on urban adjustment</b>									
The method used to adjust QMED for urbanisation published in Kjeldsen (2010) <b>Error! Bookmark not defined.</b> in which PRUAF is calculated from BFIHOST is not correctly applied in WINFAP-FEH v3.0.003. Significant differences occur only on urban catchments that are highly permeable. This is discussed in Wallingford HydroSolutions (2016) <sup>3</sup> .									

<sup>3</sup> Wallingford HydroSolutions (2016). WINFAP 4 Urban adjustment procedures.

### 4.3 Search for donor sites for QMED (if applicable)

<p>Comment on potential donor sites</p>	<p>The 5 closest donor sites are listed in Section 2.4. Gauging station 39034 (Evenlode @ Cassington Mill) has been selected as this is the only catchment with similar geology and to DS_R01 – with majority limestone and permeable bedrock. This is reflected in the high value of BFI HOST. Therefore the relationship between the observed and Catchment Descriptor values of QMED (ratio of 1.07) is incorporated in to the QMED estimation. If all 6 geographically nearest gauging stations are used, the donor adjusted estimate for QMED is 0.237. We are therefore using a more conservative (higher) estimate of donor adjusted QMED based upon study of the underlying geology of the local catchments.</p>
---	--

Station	Distance	URBEKT	Use QMED Obs Debarred	QMED Obs	QMED Debarred	QMED CD's	CentroidX	CentroidY
1 110649750 (24300 @ Dn_01)	0.01		<input type="checkbox"/>				457323	226397
2 33005 (Bedford Close @ Thornborough 11.34)	0.014		<input type="checkbox"/>	21.800	21.459	35.179	467160	221532
3 39031 (Chewell @ Enslow Mill)	17.72	0.024	<input type="checkbox"/>	19.300	19.550	33.724	446559	240457
4 33019 (Tove @ Capperthorn Bridge)	22.39	0.016	<input type="checkbox"/>	17.040	16.734	19.610	463130	247558
5 39035 (Chewell @ Barkway)	24.70	0.016	<input type="checkbox"/>	16.731	16.461	22.962	448515	249775
6 39034 (Evenlode @ Cassington Mill)	24.86	0.014	<input type="checkbox"/>	20.800	20.059	18.769	433552	223000
7 39032 (Thames @ Oak View)	29.62	0.020	<input type="checkbox"/>	148.914	141.173	19.098	438525	213290
8 54105 (Stow (walk-1) @ Shipston)	34.07	0.011	<input type="checkbox"/>	29.460	29.110	22.970	424858	236672

### 4.4 Derivation of pooling groups and growth curves

The pooling group has been generated using WINFAP v.4. Station 206006 (Analog @ Recorder) has been removed due to old dataset and 72014 (Conder @ Galgate) has been added to being a suitable small catchment. The pooling group can be found in **Appendix 01** along with the details of the application of the permeable adjustment method. Only the GL distribution can be applied to the permeable adjustment method.

### 4.5 Derivation of flood growth curves at subject sites – Perm adjusted GL distribution

Site code	Flood peak (m <sup>3</sup> /s) for the following return periods (in years)									
	2	5	10	20	25	50	100	200	500	1000
	Flood peak (m <sup>3</sup> /s) for the following AEP (%) events									
	50	20	10	5	3.33	2	1.33	1	0.5	0.1
DS_R01	1.000	1.445	1.784	2.161	2.294	2.751	3.285	3.915	4.926	5.854

### 4.6 Flood estimates from the statistical method

Site code	Flood peak (m <sup>3</sup> /s) for the following return periods (in years)									
	2	5	10	20	25	50	100	200	500	1000
	Flood peak (m <sup>3</sup> /s) for the following AEP (%) events									
	50	20	10	5	3.33	2	1.33	1	0.5	0.1
DS_R01	<b>0.30</b>	<b>0.43</b>	<b>0.53</b>	<b>0.64</b>	<b>0.68</b>	<b>0.82</b>	<b>0.98</b>	<b>1.17</b>	<b>1.47</b>	<b>1.74</b>

## **6 REVITALISED FLOOD HYDROGRAPH 2 (REFH2) METHOD**

### **6.1 Application of ReFH2 method**

The ReFH2 (version 2.3) method has been applied at all lumped and sub-catchments. The ReFH2 identified critical storm duration for the US-R01 (key reach for the site) catchment has been applied to all other catchments in the study so that uniform storm durations can be applied throughout the hydraulic model.

The ReFH2 full details and parameterisation can be found in **Appendix 02**.



## 7 DISCUSSION AND SUMMARY OF RESULTS

### 7.1 Comparison of results from different methods

The table below shows the comparison in ReFH2 and statistical peak flows for the lumped downstream catchment.

Site code	DS_R01 Flood peak (m <sup>3</sup> /s) for the following return periods (in years)									
	2	5	10	20	25	50	100	200	500	1000
	DS_R01 Flood peak (m <sup>3</sup> /s) for the following AEP (%) events									
	50	20	10	5	3.33	2	1.33	1	0.5	0.1
Statistical Method	<b>0.30</b>	<b>0.43</b>	<b>0.53</b>	<b>0.64</b>	<b>0.68</b>	<b>0.82</b>	<b>0.98</b>	<b>1.17</b>	<b>1.47</b>	<b>1.74</b>
ReFH2				<b>0.84</b>			<b>1.24</b>			<b>2.19</b>

Final Peak flows for all sub catchments shown below.

Design Event	Catchment			
	Total	Reach 1	Reach 2	Lateral
	7.60 km <sup>2</sup>	3.88 km <sup>2</sup>	0.53 km <sup>2</sup>	3.19 km <sup>2</sup>
1 in 20	0.64	0.33	0.04	0.27
1 in 100	0.98	0.50	0.07	0.41
1 in 100 + 15%CC	1.13	0.58	0.08	0.47
1 in 100 + 25%CC	1.23	0.63	0.09	0.51
1 in 1000	1.74	0.89	0.12	0.73

Due to the catchment being permeable, it is deemed more appropriate to use the peak flows from the statistical method analysis. These include allocation for the permeable adjustment method and adjusted QMED from a suitable donor catchment with similar catchment characteristics and geology. These significant elements of the catchment are not considered fully by the ReFH2 calculations.

The US\_R01 ReFH2 (key catchment) hydrograph shape has been used for all catchments to allow for the correct estimation of the lateral inflows. The same hydrograph shape must be applied for all sub catchments and the lumped catchment as the lateral inflow is calculated by subtracting the two upstream sub catchments from the downstream lumped catchment flow. This lateral inflow divided and applied at 10 discrete locations along the model reach as shown in the accompanying hydraulic modelling report.


The ReFH2 hydrograph is scaled using the relationship of the ReFH2 and statistical method peak flows for DS\_R01, as this is the only location where the statistical method has been applied. The scaling factor for each sub catchment is based upon the relative catchment areas.

The final scaled hydrographs are contained in **Appendix 03**.


# Appendix 3

Watercourse Survey

LONG SECTION KEY:  
 WATER LEVEL —————  
 BED LEVEL —————  
 SILT LEVEL - - - - -  
 STRUCTURES ————  
 RIGHT BANK ————  
 LEFT BANK - - - - -



Scale: 1:2000H 1:100V




Scale: 1:2000




Ordnance Survey (c) Crown Copyright 2021. All rights reserved.

NOTES:


SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
AB	Access Bridge	AB	Access Bridge
AD	Access Dam	AD	Access Dam
BE	Bank Edge	BE	Bank Edge
BR	Bridge	BR	Bridge
BU	Bulkhead	BU	Bulkhead
CH	Channel	CH	Channel
CL	Channel Line	CL	Channel Line
CO	Construction	CO	Construction
CR	Crack	CR	Crack
CS	Construction Site	CS	Construction Site
CU	Construction Unit	CU	Construction Unit
DA	Dam	DA	Dam
DB	Dam Bank	DB	Dam Bank
DC	Dam Crest	DC	Dam Crest
DD	Dam Downstream	DD	Dam Downstream
DE	Dam Edge	DE	Dam Edge
DF	Dam Foot	DF	Dam Foot
DG	Dam Gate	DG	Dam Gate
DH	Dam Head	DH	Dam Head
DI	Dam Inlet	DI	Dam Inlet
DJ	Dam Outlet	DJ	Dam Outlet
DK	Dam Pier	DK	Dam Pier
DL	Dam Pile	DL	Dam Pile
DM	Dam Road	DM	Dam Road
DN	Dam Structure	DN	Dam Structure
DO	Dam Wall	DO	Dam Wall
DP	Dam Weir	DP	Dam Weir
DQ	Dam Work	DQ	Dam Work
DR	Dam Zone	DR	Dam Zone
DS	Dam Structure	DS	Dam Structure
DT	Dam Structure	DT	Dam Structure
DU	Dam Structure	DU	Dam Structure
DV	Dam Structure	DV	Dam Structure
DW	Dam Structure	DW	Dam Structure
DX	Dam Structure	DX	Dam Structure
DY	Dam Structure	DY	Dam Structure
DZ	Dam Structure	DZ	Dam Structure
EA	Dam Structure	EA	Dam Structure
EB	Dam Structure	EB	Dam Structure
EC	Dam Structure	EC	Dam Structure
ED	Dam Structure	ED	Dam Structure
EE	Dam Structure	EE	Dam Structure
EF	Dam Structure	EF	Dam Structure
EG	Dam Structure	EG	Dam Structure
EH	Dam Structure	EH	Dam Structure
EI	Dam Structure	EI	Dam Structure
EJ	Dam Structure	EJ	Dam Structure
EK	Dam Structure	EK	Dam Structure
EL	Dam Structure	EL	Dam Structure
EM	Dam Structure	EM	Dam Structure
EN	Dam Structure	EN	Dam Structure
EO	Dam Structure	EO	Dam Structure
EP	Dam Structure	EP	Dam Structure
EQ	Dam Structure	EQ	Dam Structure
ER	Dam Structure	ER	Dam Structure
ES	Dam Structure	ES	Dam Structure
ET	Dam Structure	ET	Dam Structure
EU	Dam Structure	EU	Dam Structure
EV	Dam Structure	EV	Dam Structure
EW	Dam Structure	EW	Dam Structure
EX	Dam Structure	EX	Dam Structure
EY	Dam Structure	EY	Dam Structure
EZ	Dam Structure	EZ	Dam Structure
FA	Dam Structure	FA	Dam Structure
FB	Dam Structure	FB	Dam Structure
FC	Dam Structure	FC	Dam Structure
FD	Dam Structure	FD	Dam Structure
FE	Dam Structure	FE	Dam Structure
FF	Dam Structure	FF	Dam Structure
FG	Dam Structure	FG	Dam Structure
FH	Dam Structure	FH	Dam Structure
FI	Dam Structure	FI	Dam Structure
FJ	Dam Structure	FJ	Dam Structure
FK	Dam Structure	FK	Dam Structure
FL	Dam Structure	FL	Dam Structure
FM	Dam Structure	FM	Dam Structure
FN	Dam Structure	FN	Dam Structure
FO	Dam Structure	FO	Dam Structure
FP	Dam Structure	FP	Dam Structure
FQ	Dam Structure	FQ	Dam Structure
FR	Dam Structure	FR	Dam Structure
FS	Dam Structure	FS	Dam Structure
FT	Dam Structure	FT	Dam Structure
FU	Dam Structure	FU	Dam Structure
FV	Dam Structure	FV	Dam Structure
FW	Dam Structure		




REA01\_00000  
CHAINAGE 0.320  
457619.81E 224207.62N BEARING 238  
Culvert Entrance  
29/07/2021




REA01\_00015  
CHAINAGE 14.661  
457617.85E 224221.31N BEARING 244  
Access Bridge  
29/07/2021




REA01\_00115  
CHAINAGE 115.179  
457648.79E 224292.83N BEARING 286  
Open Channel  
29/07/2021




REA01\_00318  
CHAINAGE 318.268  
457639.97E 224491.13N BEARING 276  
Other Structure - Dilapidated Footbridge  
29/07/2021



REA01\_00546  
CHAINAGE 546.420  
457778.30E 224697.27N BEARING 297  
Open Channel  
29/07/2021



REA01\_00608  
CHAINAGE 608.071  
457809.61E 224757.14N BEARING 279  
Footbridge  
29/07/2021



REA01\_00660  
CHAINAGE 660.291  
457851.89E 224791.09N BEARING 292  
Charlotte Avenue - Road Bridge  
29/07/2021

CROSS SECTION KEY:  
WATER LEVEL  
BED LEVEL  
SILT LEVEL

NOTES:  
ALL CROSS SECTIONS SHOWN AS A REPRESENTATIVE SECTION UNLESS OTHERWISE STATED.  
ALL CROSS SECTIONS HAVE BEEN CONDUCTED ON A DRY CHANNEL UNLESS OTHERWISE STATED.  
ALL DIMENSIONS & CHAINAGE ARE IN METRES UNLESS OTHERWISE STATED.

SURVEY LEGEND			
AB	AB AREA	AB	AB AREA
B	BANK	B	BANK
B1	BANK 1	B1	BANK 1
B2	BANK 2	B2	BANK 2
B3	BANK 3	B3	BANK 3
B4	BANK 4	B4	BANK 4
B5	BANK 5	B5	BANK 5
B6	BANK 6	B6	BANK 6
B7	BANK 7	B7	BANK 7
B8	BANK 8	B8	BANK 8
B9	BANK 9	B9	BANK 9
B10	BANK 10	B10	BANK 10
B11	BANK 11	B11	BANK 11
B12	BANK 12	B12	BANK 12
B13	BANK 13	B13	BANK 13
B14	BANK 14	B14	BANK 14
B15	BANK 15	B15	BANK 15
B16	BANK 16	B16	BANK 16
B17	BANK 17	B17	BANK 17
B18	BANK 18	B18	BANK 18
B19	BANK 19	B19	BANK 19
B20	BANK 20	B20	BANK 20
B21	BANK 21	B21	BANK 21
B22	BANK 22	B22	BANK 22
B23	BANK 23	B23	BANK 23
B24	BANK 24	B24	BANK 24
B25	BANK 25	B25	BANK 25
B26	BANK 26	B26	BANK 26
B27	BANK 27	B27	BANK 27
B28	BANK 28	B28	BANK 28
B29	BANK 29	B29	BANK 29
B30	BANK 30	B30	BANK 30
B31	BANK 31	B31	BANK 31
B32	BANK 32	B32	BANK 32
B33	BANK 33	B33	BANK 33
B34	BANK 34	B34	BANK 34
B35	BANK 35	B35	BANK 35
B36	BANK 36	B36	BANK 36
B37	BANK 37	B37	BANK 37
B38	BANK 38	B38	BANK 38
B39	BANK 39	B39	BANK 39
B40	BANK 40	B40	BANK 40
B41	BANK 41	B41	BANK 41
B42	BANK 42	B42	BANK 42
B43	BANK 43	B43	BANK 43
B44	BANK 44	B44	BANK 44
B45	BANK 45	B45	BANK 45
B46	BANK 46	B46	BANK 46
B47	BANK 47	B47	BANK 47
B48	BANK 48	B48	BANK 48
B49	BANK 49	B49	BANK 49
B50	BANK 50	B50	BANK 50
B51	BANK 51	B51	BANK 51
B52	BANK 52	B52	BANK 52
B53	BANK 53	B53	BANK 53
B54	BANK 54	B54	BANK 54
B55	BANK 55	B55	BANK 55
B56	BANK 56	B56	BANK 56
B57	BANK 57	B57	BANK 57
B58	BANK 58	B58	BANK 58
B59	BANK 59	B59	BANK 59
B60	BANK 60	B60	BANK 60
B61	BANK 61	B61	BANK 61
B62	BANK 62	B62	BANK 62
B63	BANK 63	B63	BANK 63
B64	BANK 64	B64	BANK 64
B65	BANK 65	B65	BANK 65
B66	BANK 66	B66	BANK 66
B67	BANK 67	B67	BANK 67
B68	BANK 68	B68	BANK 68
B69	BANK 69	B69	BANK 69
B70	BANK 70	B70	BANK 70
B71	BANK 71	B71	BANK 71
B72	BANK 72	B72	BANK 72
B73	BANK 73	B73	BANK 73
B74	BANK 74	B74	BANK 74
B75	BANK 75	B75	BANK 75
B76	BANK 76	B76	BANK 76
B77	BANK 77	B77	BANK 77
B78	BANK 78	B78	BANK 78
B79	BANK 79	B79	BANK 79
B80	BANK 80	B80	BANK 80
B81	BANK 81	B81	BANK 81
B82	BANK 82	B82	BANK 82
B83	BANK 83	B83	BANK 83
B84	BANK 84	B84	BANK 84
B85	BANK 85	B85	BANK 85
B86	BANK 86	B86	BANK 86
B87	BANK 87	B87	BANK 87
B88	BANK 88	B88	BANK 88
B89	BANK 89	B89	BANK 89
B90	BANK 90	B90	BANK 90
B91	BANK 91	B91	BANK 91
B92	BANK 92	B92	BANK 92
B93	BANK 93	B93	BANK 93
B94	BANK 94	B94	BANK 94
B95	BANK 95	B95	BANK 95
B96	BANK 96	B96	BANK 96
B97	BANK 97	B97	BANK 97
B98	BANK 98	B98	BANK 98
B99	BANK 99	B99	BANK 99
B100	BANK 100	B100	BANK 100

REV.	ADDENDUM	CHKD.	DATE


CONTROL USED:  
10: 100%  
11: 100%  
12: 100%  
13: 100%  
14: 100%  
15: 100%  
16: 100%  
17: 100%  
18: 100%  
19: 100%  
20: 100%  
21: 100%  
22: 100%  
23: 100%  
24: 100%  
25: 100%  
26: 100%  
27: 100%  
28: 100%  
29: 100%  
30: 100%  
31: 100%  
32: 100%  
33: 100%  
34: 100%  
35: 100%  
36: 100%  
37: 100%  
38: 100%  
39: 100%  
40: 100%  
41: 100%  
42: 100%  
43: 100%  
44: 100%  
45: 100%  
46: 100%  
47: 100%  
48: 100%  
49: 100%  
50: 100%  
51: 100%  
52: 100%  
53: 100%  
54: 100%  
55: 100%  
56: 100%  
57: 100%  
58: 100%  
59: 100%  
60: 100%  
61: 100%  
62: 100%  
63: 100%  
64: 100%  
65: 100%  
66: 100%  
67: 100%  
68: 100%  
69: 100%  
70: 100%  
71: 100%  
72: 100%  
73: 100%  
74: 100%  
75: 100%  
76: 100%  
77: 100%  
78: 100%  
79: 100%  
80: 100%  
81: 100%  
82: 100%  
83: 100%  
84: 100%  
85: 100%  
86: 100%  
87: 100%  
88: 100%  
89: 100%  
90: 100%  
91: 100%  
92: 100%  
93: 100%  
94: 100%  
95: 100%  
96: 100%  
97: 100%  
98: 100%  
99: 100%  
100: 100%

STORM GEOMATICS  
Tel: 01608 664910  
mail@storm-geomatics.com  
www.storm-geomatics.com


RICS  
ICES  
Construction

CLIENT: Vectos  
PROJECT: NW Bicester Survey  
SITE: Reach 01  
Charlotte Ave, Bicester OX27 8BL  
REA01\_00000 to REA01\_00660  
Sheet 1 of 3


SURVEYED BY: Storm Geomatics Ltd		Project Ref: 21FD1391	
SURVEY DATE: July 2021			
SCALE: 1:100 (A3 Sheet)	DRN: MBM	CHKD: SRD	
DATUM: OS Newlyn (15)	DATE: 06/08/2021	DATE: 12/08/2021	
GRID: OS Grid (15)	DRAWING NO: 21FD1391/01	REV: -	




REA01\_00725  
CHAINAGE\_725.127  
457850.40E 224861.60N BEARING 280  
Footbridge  
29/07/2021




REA01\_00777  
CHAINAGE\_777.027  
457882.59E 224886.64N BEARING 306  
Open Channel  
29/07/2021




REA01\_00844  
CHAINAGE\_844.252  
457928.82E 224927.46N BEARING 317  
Open Channel  
29/07/2021




REA01\_00862  
CHAINAGE\_862.305  
457942.46E 224939.24N BEARING 317  
Open Channel  
29/07/2021




REA01\_00925  
CHAINAGE\_925.003  
457981.13E 224988.69N BEARING 316  
Access Bridge  
29/07/2021




REA01\_00946  
CHAINAGE\_946.246  
457989.31E 225002.41N BEARING 343  
Footbridge  
29/07/2021




REA01\_00993  
CHAINAGE\_993.341  
458029.16E 225030.65N BEARING 314  
Open Channel  
29/07/2021




REA01\_01023  
CHAINAGE\_1023.172  
458048.29E 225043.24N BEARING 350  
Footbridge  
29/07/2021



REA01\_01028  
CHAINAGE\_1028.168  
458053.48E 225046.05N BEARING 346  
Other Structure - Sheep-Dip  
29/07/2021



REA01\_01068  
CHAINAGE\_1067.971  
458094.52E 225061.17N BEARING 324  
Culvert Entrance  
29/07/2021



REA01\_01073  
CHAINAGE\_1072.775  
458098.86E 225062.89N BEARING 326  
Open Channel  
29/07/2021

CROSS SECTION KEY:  
WATER LEVEL  
BED LEVEL  
SILT LEVEL

NOTES:

SYMBOL	DESCRIPTION
1	Proposed
2	Existing
3	As Shown
4	Not Shown
5	Not to Scale
6	Not to Scale
7	Not to Scale
8	Not to Scale
9	Not to Scale
10	Not to Scale
11	Not to Scale
12	Not to Scale
13	Not to Scale
14	Not to Scale
15	Not to Scale
16	Not to Scale
17	Not to Scale
18	Not to Scale
19	Not to Scale
20	Not to Scale
21	Not to Scale
22	Not to Scale
23	Not to Scale
24	Not to Scale
25	Not to Scale
26	Not to Scale
27	Not to Scale
28	Not to Scale
29	Not to Scale
30	Not to Scale
31	Not to Scale
32	Not to Scale
33	Not to Scale
34	Not to Scale
35	Not to Scale
36	Not to Scale
37	Not to Scale
38	Not to Scale
39	Not to Scale
40	Not to Scale
41	Not to Scale
42	Not to Scale
43	Not to Scale
44	Not to Scale
45	Not to Scale
46	Not to Scale
47	Not to Scale
48	Not to Scale
49	Not to Scale
50	Not to Scale
51	Not to Scale
52	Not to Scale
53	Not to Scale
54	Not to Scale
55	Not to Scale
56	Not to Scale
57	Not to Scale
58	Not to Scale
59	Not to Scale
60	Not to Scale
61	Not to Scale
62	Not to Scale
63	Not to Scale
64	Not to Scale
65	Not to Scale
66	Not to Scale
67	Not to Scale
68	Not to Scale
69	Not to Scale
70	Not to Scale
71	Not to Scale
72	Not to Scale
73	Not to Scale
74	Not to Scale
75	Not to Scale
76	Not to Scale
77	Not to Scale
78	Not to Scale
79	Not to Scale
80	Not to Scale
81	Not to Scale
82	Not to Scale
83	Not to Scale
84	Not to Scale
85	Not to Scale
86	Not to Scale
87	Not to Scale
88	Not to Scale
89	Not to Scale
90	Not to Scale
91	Not to Scale
92	Not to Scale
93	Not to Scale
94	Not to Scale
95	Not to Scale
96	Not to Scale
97	Not to Scale
98	Not to Scale
99	Not to Scale
100	Not to Scale

CONTROL USED:  
Easting: 457850.40  
Northing: 224861.60  
Datum: NZGD 2011



CLIENT: Vectos

PROJECT: NW Bicester Survey


SITE: Reach 02  
Charlotte Ave, Bicester OX27 8BL  
REA01\_00725 to REA01\_01073  
Sheet 2 of 3

SURVEYED BY: Storm Geomatics Ltd  
SURVEY DATE: July 2021  
SCALE: 1:100 (A0 Sheet)  
DATUM: OS Newlyn (15)  
GRID: OS Grid (15)


PROJECT NO: 21FD1391/02

DATE: 06/08/2021  
DRAWING NO: 21FD1391/02


DATE: 12/08/2021  
REV: 1




REA01\_01082  
CHAINAGE\_1081.881  
458103.48E 225065.78N BEARING 340  
Culvert Entrance  
29/07/2021




REA01\_01120  
CHAINAGE\_1119.997  
458140.85E 225079.54N BEARING 327  
Culvert Entrance  
29/07/2021




REA01\_01141  
CHAINAGE\_1141.211  
458165.63E 225094.68N BEARING 290  
Footbridge  
29/07/2021




REA01\_01227  
CHAINAGE\_1227.121  
458224.78E 225150.67N BEARING 306  
Open Channel  
29/07/2021




REA01\_01330  
CHAINAGE\_1330.036  
458278.86E 225249.12N BEARING 247  
Open Channel  
29/07/2021




REA01\_01399  
CHAINAGE\_1399.031  
458245.06E 225307.74N BEARING 254  
Culvert Entrance  
29/07/2021



REA01\_01500  
CHAINAGE\_1500.238  
458202.32E 225399.93N BEARING 243  
Access Bridge  
29/07/2021



REA01\_01590  
CHAINAGE\_1589.872  
458150.56E 225481.99N BEARING 229  
Access Bridge  
29/07/2021



REA01\_01668  
CHAINAGE\_1668.084  
458122.03E 225543.27N BEARING 248  
Open Channel  
29/07/2021

CROSS SECTION KEY:  
WATER LEVEL  
BED LEVEL  
SILT LEVEL

NOTES:

ALL CROSS SECTIONS SHOULD BE A REPRESENTATIVE SECTION UNLESS OTHERWISE STATED.  
ALL LEVELS ARE REFERRED TO THE DATUM UNLESS OTHERWISE STATED.  
ALL DIMENSIONS & CHANGES ARE IN METRES UNLESS OTHERWISE STATED.

SURVEY LEGEND	
AB	AB AREA
B	B AREA
B1	B1 AREA
B2	B2 AREA
B3	B3 AREA
B4	B4 AREA
B5	B5 AREA
B6	B6 AREA
B7	B7 AREA
B8	B8 AREA
B9	B9 AREA
B10	B10 AREA
B11	B11 AREA
B12	B12 AREA
B13	B13 AREA
B14	B14 AREA
B15	B15 AREA
B16	B16 AREA
B17	B17 AREA
B18	B18 AREA
B19	B19 AREA
B20	B20 AREA
B21	B21 AREA
B22	B22 AREA
B23	B23 AREA
B24	B24 AREA
B25	B25 AREA
B26	B26 AREA
B27	B27 AREA
B28	B28 AREA
B29	B29 AREA
B30	B30 AREA
B31	B31 AREA
B32	B32 AREA
B33	B33 AREA
B34	B34 AREA
B35	B35 AREA
B36	B36 AREA
B37	B37 AREA
B38	B38 AREA
B39	B39 AREA
B40	B40 AREA
B41	B41 AREA
B42	B42 AREA
B43	B43 AREA
B44	B44 AREA
B45	B45 AREA
B46	B46 AREA
B47	B47 AREA
B48	B48 AREA
B49	B49 AREA
B50	B50 AREA
B51	B51 AREA
B52	B52 AREA
B53	B53 AREA
B54	B54 AREA
B55	B55 AREA
B56	B56 AREA
B57	B57 AREA
B58	B58 AREA
B59	B59 AREA
B60	B60 AREA
B61	B61 AREA
B62	B62 AREA
B63	B63 AREA
B64	B64 AREA
B65	B65 AREA
B66	B66 AREA
B67	B67 AREA
B68	B68 AREA
B69	B69 AREA
B70	B70 AREA
B71	B71 AREA
B72	B72 AREA
B73	B73 AREA
B74	B74 AREA
B75	B75 AREA
B76	B76 AREA
B77	B77 AREA
B78	B78 AREA
B79	B79 AREA
B80	B80 AREA
B81	B81 AREA
B82	B82 AREA
B83	B83 AREA
B84	B84 AREA
B85	B85 AREA
B86	B86 AREA
B87	B87 AREA
B88	B88 AREA
B89	B89 AREA
B90	B90 AREA
B91	B91 AREA
B92	B92 AREA
B93	B93 AREA
B94	B94 AREA
B95	B95 AREA
B96	B96 AREA
B97	B97 AREA
B98	B98 AREA
B99	B99 AREA
B100	B100 AREA

CONTROL USED:  
E6: 100M 1:1000  
E6: 100M 1:1000



CLIENT: Vectos


PROJECT: NW Bicester Survey

SITE: Reach 01  
Charlotte Ave, Bicester OX27 8BL  
REA01\_01082 to REA01\_01668  
Sheet 3 of 3


SURVEYED BY: Storm Geomatics Ltd  
SURVEY DATE: July 2021  
SCALE: 1:100 (A0 Sheet)  
DATUM: OS Newlyn (15)  
GRID: OS Grid (15)

DRN: MBM  
DATE: 06/08/2021  
DRAWING NO: 21FD1391/03

CHKD: SRD  
DATE: 12/08/2021  
REV: -



Scale: 1:2000H 1:100V



Scale: 1:2000

LONG SECTION KEY:  
 WATER LEVEL  
 BED LEVEL  
 SILT LEVEL  
 STRUCTURES  
 RIGHT BANK  
 LEFT BANK

VERTICAL LOOKING DOWNSTREAM  
 POINTS INDICATED BY 'D'  
 LOWER SECTION AND ADDITIONAL  
 POINTS BETWEEN SECTIONS

Ordnance Survey (c) Crown Copyright 2021. All rights reserved.

NOTES:

SURVEY LEGEND			
AB	AB AREA	AB	AB AREA
B	BANK	B	BANK
B1	BANK 1	B1	BANK 1
B2	BANK 2	B2	BANK 2
B3	BANK 3	B3	BANK 3
B4	BANK 4	B4	BANK 4
B5	BANK 5	B5	BANK 5
B6	BANK 6	B6	BANK 6
B7	BANK 7	B7	BANK 7
B8	BANK 8	B8	BANK 8
B9	BANK 9	B9	BANK 9
B10	BANK 10	B10	BANK 10
B11	BANK 11	B11	BANK 11
B12	BANK 12	B12	BANK 12
B13	BANK 13	B13	BANK 13
B14	BANK 14	B14	BANK 14
B15	BANK 15	B15	BANK 15
B16	BANK 16	B16	BANK 16
B17	BANK 17	B17	BANK 17
B18	BANK 18	B18	BANK 18
B19	BANK 19	B19	BANK 19
B20	BANK 20	B20	BANK 20
B21	BANK 21	B21	BANK 21
B22	BANK 22	B22	BANK 22
B23	BANK 23	B23	BANK 23
B24	BANK 24	B24	BANK 24
B25	BANK 25	B25	BANK 25
B26	BANK 26	B26	BANK 26
B27	BANK 27	B27	BANK 27
B28	BANK 28	B28	BANK 28
B29	BANK 29	B29	BANK 29
B30	BANK 30	B30	BANK 30
B31	BANK 31	B31	BANK 31
B32	BANK 32	B32	BANK 32
B33	BANK 33	B33	BANK 33
B34	BANK 34	B34	BANK 34
B35	BANK 35	B35	BANK 35
B36	BANK 36	B36	BANK 36
B37	BANK 37	B37	BANK 37
B38	BANK 38	B38	BANK 38
B39	BANK 39	B39	BANK 39
B40	BANK 40	B40	BANK 40
B41	BANK 41	B41	BANK 41
B42	BANK 42	B42	BANK 42
B43	BANK 43	B43	BANK 43
B44	BANK 44	B44	BANK 44
B45	BANK 45	B45	BANK 45
B46	BANK 46	B46	BANK 46
B47	BANK 47	B47	BANK 47
B48	BANK 48	B48	BANK 48
B49	BANK 49	B49	BANK 49
B50	BANK 50	B50	BANK 50
B51	BANK 51	B51	BANK 51
B52	BANK 52	B52	BANK 52
B53	BANK 53	B53	BANK 53
B54	BANK 54	B54	BANK 54
B55	BANK 55	B55	BANK 55
B56	BANK 56	B56	BANK 56
B57	BANK 57	B57	BANK 57
B58	BANK 58	B58	BANK 58
B59	BANK 59	B59	BANK 59
B60	BANK 60	B60	BANK 60
B61	BANK 61	B61	BANK 61
B62	BANK 62	B62	BANK 62
B63	BANK 63	B63	BANK 63
B64	BANK 64	B64	BANK 64
B65	BANK 65	B65	BANK 65
B66	BANK 66	B66	BANK 66
B67	BANK 67	B67	BANK 67
B68	BANK 68	B68	BANK 68
B69	BANK 69	B69	BANK 69
B70	BANK 70	B70	BANK 70
B71	BANK 71	B71	BANK 71
B72	BANK 72	B72	BANK 72
B73	BANK 73	B73	BANK 73
B74	BANK 74	B74	BANK 74
B75	BANK 75	B75	BANK 75
B76	BANK 76	B76	BANK 76
B77	BANK 77	B77	BANK 77
B78	BANK 78	B78	BANK 78
B79	BANK 79	B79	BANK 79
B80	BANK 80	B80	BANK 80
B81	BANK 81	B81	BANK 81
B82	BANK 82	B82	BANK 82
B83	BANK 83	B83	BANK 83
B84	BANK 84	B84	BANK 84
B85	BANK 85	B85	BANK 85
B86	BANK 86	B86	BANK 86
B87	BANK 87	B87	BANK 87
B88	BANK 88	B88	BANK 88
B89	BANK 89	B89	BANK 89
B90	BANK 90	B90	BANK 90
B91	BANK 91	B91	BANK 91
B92	BANK 92	B92	BANK 92
B93	BANK 93	B93	BANK 93
B94	BANK 94	B94	BANK 94
B95	BANK 95	B95	BANK 95
B96	BANK 96	B96	BANK 96
B97	BANK 97	B97	BANK 97
B98	BANK 98	B98	BANK 98
B99	BANK 99	B99	BANK 99
B100	BANK 100	B100	BANK 100

REV.	AMENDMENT	DRN	CHKD	DATE

CONTROL USED:  
 1:1  
 1:1  
 1:1  
 1:1

STORM GEOMATICS  
 Tel: 01608 664910  
 mail@storm-geomatrics.com  
 www.storm-geomatrics.com

RICS  
 ICES  
 Construction

CLIENT: Vectos

PROJECT: NW Bicester Survey

Reach 02  
 Charlotte Ave, Bicester OX27 8BL  
 Long Section & Location Plan  
 Sheet 1 of 1


SURVEYED BY: Storm Geomatics Ltd  
 SURVEY DATE: July 2021  
 SCALE: As Shown (A0 Sheet)  
 DATUM: OS Grid (15)  
 GRID: OS Grid (15)

DRN: MBM  
 DATE: 06/08/2021  
 DRAWING NO.: 21FD1391-07


CHKD: SRD  
 DATE: 12/08/2021  
 REV: -









REA02\_00351  
CHAINAGE 351.320  
457560.05E 225040.77N BEARING 199  
Open Channel  
27/07/2021




REA02\_00444  
CHAINAGE 443.550  
457471.91E 225066.60N BEARING 200  
Open Channel  
27/07/2021




REA02\_00579  
CHAINAGE 578.866  
457359.30E 225134.76N BEARING 213  
Open Channel  
27/07/2021




REA02\_00690  
CHAINAGE 689.506  
457290.50E 225218.58N BEARING 214  
Culvert Entrance  
27/07/2021




REA02\_00785  
CHAINAGE 784.866  
457195.78E 225254.49N BEARING 191  
Open Channel  
27/07/2021




REA02\_00946  
CHAINAGE 946.059  
457044.50E 225291.71N BEARING 205  
Open Channel  
27/07/2021




REA02\_01080  
CHAINAGE 1089.478  
456969.35E 225401.22N BEARING 240  
Open Channel  
27/07/2021



REA02\_01240  
CHAINAGE 1240.402  
456898.26E 225533.05N BEARING 239  
Footbridge  
27/07/2021



REA02\_01264  
CHAINAGE 1263.973  
456874.63E 225648.92N BEARING 222  
Culvert Entrance  
27/07/2021



REA02\_01472  
CHAINAGE 1471.508  
456735.22E 225677.07N BEARING 188  
Open Channel  
27/07/2021

**CROSS SECTION KEY:**  
 WATER LEVEL —————  
 BED LEVEL —————  
 SILT LEVEL - - - - -

**NOTES:**  
 ALL CROSS SECTIONS SHOWN ARE A REPRESENTATIVE SECTION AND NOT A COMPLETE CROSS SECTION.  
 ALL DIMENSIONS & CHANGING ARE IN METERS UNLESS OTHERWISE STATED.

**SURVEY LEGEND:**

SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
...	...	...	...

**CONTROL USED:**  
 10: 2020/07/18 Easting Northing Height  
 10: 47834.006 22478.158 84.964

**STORM GEOMATICS**  
 Tel: 01608 664910  
 mail@storm-geomatics.com  
 www.storm-geomatics.com

**CLIENT:** Vectos

**PROJECT:** NW Bicester Survey

**SITE:** Reach 02  
 Charlotte Ave, Bicester OX27 8BL  
 REA02\_00351 to REA02\_01472  
 Sheet 2 of 2

**SURVEYED BY:** Storm Geomatics Ltd *Project Ref: 21FD1391*

**SURVEY DATE:** July 2021

**SCALE:** 1:100 (A0 Sheet) **DRN:** MBM **CHKD:** SRD

**DATUM:** OS Newlyn (15) **DATE:** 06/08/2021 **DATE:** 12/08/2021

**GRID:** OS Grid (15) **DRAWING NO.:** 21FD1391/06 **REV.:** 1

**CAD FILENAME:** REA02\_00351.dwg





# Appendix 4

Flood Mapping














## Contact

---

### **London**

Network Building,  
97 Tottenham Court Road,  
London W1T 4TP.  
Tel: 020 7580 7373

### **Bristol**

5th Floor, 4 Colston Avenue,  
Bristol BS1 4ST  
Tel: 0117 203 5240

### **Cardiff**

Helmont House, Churchill Way,  
Cardiff CF10 2HE  
Tel: 029 2072 0860

### **Exeter**

6 Victory House,  
Dean Clarke Gardens,  
Exeter EX2 4AA  
Tel: 01392 422 315

### **Birmingham**

Great Charles Street,  
Birmingham B3 3JY  
Tel: 0121 2895 624

### **Manchester**

Oxford Place, 61 Oxford Street,  
Manchester M1 6EQ.  
Tel: 0161 228 1008

### **Leeds**

7 Park Row, Leeds LS1 5HD  
Tel: 0113 512 0293

### **Bonn**

Stockenstrasse 5, 53113,  
Bonn, Germany  
Tel: +49 176 8609 1360  
[www.vectos.eu](http://www.vectos.eu)

### **Registered Office**

**Vectos (South) Limited**  
**Network Building,**  
**97 Tottenham Court Road,**  
**London W1T 4TP**  
**Company no. 7591661**