

Group D Various M 500 10 0 B2 6 6 6 6 6 113.1 40+ Reasonable growth potential of Ash.

ref.	Species	Age Class	g/m/g	Height	Lower crown height	Grade	Crown Spread N	Crown Spread S	Crown Spread E	Crown Spread W	RPA radius	RPA (m2)	Remaining Contribution	Condition	Comments	Recommendations made at time of survey, irrespective of any layout
Group E	Various	М	400	10	0	B2	5	5	5	5	4.8	72.4	40+	Reasonable	Partially lapsed hedge comprising Sycamore, Ash, Hawthorn and Field Maple. Historically cut at 1.5m. Historically laid.	No work required but could be cut as a hedge.
3899	Goat Willow	SM	180	8	0	C1	3	3	3	3	2.16	14.7	20+	Reasonable	Natural generation. Unlikely to be suitable for retention.	Fell and replace
Group F	Cherry Laurel	Υ	150	2	0	C2	0.7	0.7	0.7	0.7	1.8	10.2	40+	Good	Regularly maintained as hedge at present dimensions.	No work required

Lapsed hedge comprising Hawthorn, Field

Maple, Ash and Ivy. Historically laid and partially coppiced in places. Good screen

for adjacent development. Note future Consider controlling

Royal HaskoningDHV Deerfields Farm, Bodicote



This drawing is the property of Andrew Belson Arboricultural Consultant. Copyright is reserved by him and the drawing is issued on the condition that it is not copied, reproduced, retained nor disclosed to any unauthorized person either wholly or in part without the consent of Andrew Belson.

NOTES: Based on survey drawing R-16325 201-202 issue01

Grade A Trees Grade B Trees

Grade C Trees Grade U Trees

Extent of Root Protection Area

Extent of Canopy Extent of Canopy - Groups

Trees to be Removed Potential Extent of Canopy Shade Footprint

Suggested Build Limit

Arboricultural Constraints Root Protection Area

The Root Protection Area (RPA) is illustrated as a magenta circle or polygon around each tree or group of trees. This is the area where if the trees are retained, ideally no excavation should take place; the soil level should not be raised or lowered; no materials should be stacked; there must be no contamination and no services should be routed.

However, trees may be tolerant of some disturbance and recent advances in construction techniques can avoid causing significant damage to roots. This will depend on a number of factors including tree species and site conditions along with the type of construction methods available to the developer.

Shade or Light-Loss The shade footprint that may be cast by trees identified for retention at an

expected maximum height (given their individual circumstances) has been shown on the drawing as a hatched quadrant or general area where the quadrants merge. The shade area is based on a solar inclination of 45 deg, in line with the median suggested by BS5837. Building within the shade area can be acceptable where internal layout, fenestration or proposed use of buildings means they are not adversely affected by a lack of daylight received. Some shading may be welcomed in the summer when solar gain can make room temperatures uncomfortable. Above Ground Constraints

The height of the lower crown above ground is shown in the survey. Lifting (or raising) the crown to a set height above ground in order to install fences, achieve clearance over the driveway or allow access for plant and machinery would be an acceptable arboricultural practice. Crown spread may in its self be a constraint where it is greater than the RPA radius. Reference must be made to the Tree Constraints Plan in Appendix 'B' or the data in the tree survey schedule in Appendix 'A'.

Trees on Neighbouring Land

Trees on neighbouring ground must be taken into consideration. Future Growth

Where future radial growth is possible, this has been illustrated as a broken green line. The potential future height has been illustrated in the shade patterns drawn.

Suitability for Retention

In general, Grade 'A' and 'B' trees should be retained, especially if they offer a visual amenity to the wider community. It may be desirable to retain Grade 'C' trees where they can continue to offer a presence until they are replaced but they should not generally prevent an otherwise satisfactory layout from being achieved.

Statutory Protection

None of the trees surveyed are included in a TPO.

The site is not within a Conservation Area.

Design Objectives Design a layout that takes account of the root protection areas of retained

trees, with an aim to leave at least 5m beyond the radial extent of the RPA to make the practical execution of development feasible, (subject to other Design a layout that takes the shading and above ground constraints into account. Shady areas beyond the crown spreads of trees would be best for

car parking. Gardens must receive direct sunlight over a reasonable proportion of the area (25% is suggested) to be satisfactory.

Service routes must be located outside of the RPAs of retained trees. Implement a tree protection scheme before development (including demolition)

Make provision for replacement planting within the landscape proposals.

Rev Description Purpose of Issue

Information Only



Arboricultural Consultant 29b High Street East Uppingham Oakham

t: 01572 823637 LE15 9PY e: andrewmbelson@aol.com

Royal HaskoningDHV

Deerfields Farm, Canal Lane, Bodicote

Tree Constraints and Masterplan Assessment

AMB 29/03/2018 3406 1:500

3406.Bodicote.RHDHV.TSS