Ė.					of the proposal, site and surroundings which may influence the approach to security for the development.
					A security specialist will not be appointed prior to the close of RIBA Stage 2 to undertake a security needs assessment.
e1	Security of site and building	1	0	0	A compliant risk based security rating scheme has been used and the performance against the scheme has been confirmed by independent assessment and verification. The only scheme that appears to fit the criteria is SABRE, however to engage the BRE to undertake the assessment would be costly.
Hea 07	- Safe and healthy surrour	ndings			
	Credit	Available	Current	Potential	Comments
1	Safe access	1	0	0	Not targeted Credit awarded where the site is designed to allow for safe access for pedestrians and cyclists. Level of detail is comprehensive - refer to guidance for details. Points to consider include: cycle paths and footpaths connecting to any off site paths, paths connecting the building to the outdoor space and drop
					off areas to be located off/adjoining access road with direct access to footpath. Where delivery access areas and drop off areas exist: delivery areas are not directly accessed through general parking areas and do not cross or share pedestrian and cyclist routes and other outside amenity areas, provide a separate parking/waiting area for goods vehicles, ensure parking/turning areas are designed for simple manoeuvring.
2	Outside space	1	1	0	There is an outside space providing building users with an external amenity area. The outside space must be of an appropriate size to provide enough amenity for the predicted number of building users during coffee or lunch breaks to gather, socialise, relax and connect with the natural environment. The space is predominantly intended for building staff, but can be used by other building users where relevant and beneficial to the building users. The outside space must: • be an outdoor landscaped area, for example a garden, balcony or terrace; the majority of the space should be open to the sky • have appropriate seating areas and be non-smoking, • be located to ensure it is accessible to all building users and avoids areas that will have disturbances from sources of noise (e.g. building services, car parks, busy roads, delivery areas etc.). The architect advised that outdoor seating will be provided both within the internal courtyard area (although fairly close to some parking spaces) and within the western 'treed' area, with seating provided for approx. 20-25 people. Evidence Requirements - Architects

		Ī			Drawings detailing the above
					Drawings astaining the above
		8	4	2	Standard Health & Wellbeing Credit Total
		2	0	0	Exemplary Health & Wellbeing Credit Total
			3.50	1.75	% Health & Wellbeing Total (Standard + Exemplary)
Energ	у				
Ene 01	- Reduction of energy use	and carbo	n emissior	าร	
	Credit	Available	Current	Potential	Comments
1	Energy performance	9	2	0	Up to 9 credits can be awarded where there is an improvement in the building operational related CO ₂ emissions. The number of credits is based on the Energy Performance Ratio for New Constructions (using the BREEAM calculator). Note that negative improvement on notional figures will result in lower scores - aim to show improvement on each of the three parameters in the BRUKL (energy demand, primary energy, total CO ₂ emissions). Where more than one BRUKL is produced for a development, which is registered as a single assessment, an area-weighted average should be used to calculate the number of credits to be awarded. Each of the energy performance outputs from the BRUKL (actual CO ₂ /m² notional CO ₂ /m² etc.) must be area-weighted to produce area weighted average values which are entered into the scoring and reporting tool. Preliminary calculations indicate 2 credits can be achieved for an overall building energy performance ratio of (EPRnc) of 0.208. There is no mandatory requirement for the 'Very Good' rating
Ene 03	- External Lighting				There is no managery requirement for the very cood rating
	Credit	Available	Current	Potential	Comments
1	External lighting	1	1	0	Lights must be automatically controlled to prevent operation during daylight hours or they are/can be fitted with presence detectors (PIR). The average luminous efficacy must be 70 luminaire lumens per circuit Watt or greater. Evidence Requirements - M&E Electrical drawings indicating external lighting (light fittings and types). Schedule of external lighting and calculations for the average lumens per circuit watt M&E Performance Spec confirming lighting compliance with BREEAM Manufacturers product data sheets for each light fitting
Ene 04	- Low carbon design				
	Credit	Available	Current	Potential	Comments
1	Passive design	2	0	2	

2 Low and zero carbon technologies	1	1	0	The first credit in Hea 04 must be achieved before these credits can be pursued. These credits have not been relied upon to achieve the 'Very Good' rating. Modelling will need to be undertaken before the end of RIBA Stage 2 to confirm whether these credits are potentially achievable. Evidence Requirement – Energy Modeller Passive Design Analysis Report An energy specialist must complete a feasibility study by the end of the Concept Design to establish the most appropriate recognised local on or near site low or zero carbon energy sources for the building. Evidence Requirements - Energy Consultant LZC Feasibility Study. Study must be produced during RIBA Stage 2 by an Energy Specialist Copy of consultants CV Confirmation of the demand reduction in CO ₂ emissions from the specified technology. This should be in the form of 2 x Part L reports (a baseline using gas and grid electric and the actual case). Specification or drawings showing technology has been implemented into the design.
	13	4	2	Standard Energy Credit Total
	0	0	0	Exemplary Energy Credit Total
		2.92	1.46	% Energy Total (Standard + Exemplary)

Transport

Tra 01 - Transport assessment and travel plan

	Credit	Available	Current	Potential	Comments
1	Travel plan	2	2	0	Undertake a site specific transport assessment (or develop a travel statement) and draft travel plan, no later than Concept Design which can demonstrably be used to influence the site layout and built form. The travel plan must provide a long term management strategy which encourages more sustainable travel. The travel plan must be implemented and supported by the buildings management. The assessment must cover: a) Travel patterns and attitudes of existing users towards cycling, walking and public transport; b) Predicted travel patterns and transport impact of future users; c) Current local environment for pedestrians and cyclists (accounting for any age-related requirements of occupants and visitors); d) Reporting of the number and type of existing amenities within 500m of the site; e) Disabled access (accounting for varying levels and types of disability and visual impairment); f) Calculation of the existing public transport Accessibility Index (AI)

			g) Current facilities for cyclists. A travel plan should be developed to include proposals to increase or improve sustainable modes of transport and movement of people and goods. If the occupier is known, they should be involved in the development of the travel plan and it should be confirmed that the plan will be implemented and
			transport and movement of people and goods. If the occupier is known, they should be involved in the
			transport and movement of people and goods. If the occupier is known, they should be involved in the
			supported by the building's management in operation. Evidence Requirements - Transport Consultant
			Copy of the final Transport Assessment and Travel Plan
			•
	1		
Available	Current	Potential	Comments
			A site specific travel plan must be developed and implemented before any credits can be awarded in this issue
10	3	0	Identify and implement sustainable public, private and active transport measures, these measures include 1. The existing Accessibility Index must achieve - 1 point 2. Demonstrate an increase over the existing AI through negotiations with local bus, train or tram - 2 points OR Through the provision of a diverted bus route or new, enhanced bus stop - 3 points OR Provide a dedicated bus route or service - 3 points 3. Provide a public live transport information system in a publicly accessible area - 1 point 4. Provide electric recharging stations for 10% of the total parking capacity (minimum of 3kW) - 1 point 5. Set up a car sharing group, raise awareness of the scheme and provide priority spaces near the development entrance - 1 point 6. During RIBA Stage 1 DT consults with LA on the state of the cycling network and pedestrian routes and how to improve it. Implement one proposition chosen with the LA - 2 points 7. Install compliant cycle storage places - 1 point 8. Option 7 must be achieved before providing least two compliant cyclists facilities, showers, changing facilities, lockers, drying spaces - 1 point 9. At least three existing amenities are present - 1 point 10. Ensure a minimum of one new accessible amenity - 2 points OR Ensure more than one new accessible amenity - 3 points 11. Implement one site-specific improvement measure, not covered by the options already listed. This must be submitted for review by the BRE 1-3 points Evidence Requirements - Architect • Drawings showing charging point provision for at least 10% of the total car parking capacity for the development.
	Available 10	Available Current	Available Current Potential

			 Drawing showing the number of cycle storage spaces (1 per 10 building occupants) Drawing of storage shelter i.e. must have at least 3 sides and a roof. Drawing showing the location of the cyclist facilities i.e. lockers, changing rooms, showers Evidence Requirements - M&E The electrical spec must also state the lighting to the cycle storage area which must be compliant with BS 5489-1:2003+A2:2008 Lighting of roads and public amenity areas. The lighting must be controlled to avoid out-of-hours use and operation during daylight hours. The electrical spec must detail the electrical chargers
12	5	0	Standard Transport Credit Total
0	0	0	Exemplary Transport Credit Total
	6.04	0	% Transport Total (Standard + Exemplary)

Water

Wat	02-	w	laf	or	M	on	ite	vrino
* vat	UZ-	n.	4	CI	IAI	UII	110	

	Credit	Available	Current	Potential	Comments
1	Prerequisite				Mandatory The specification of a water meter on the mains water supply to each building; this includes instances
					where water is supplied via a borehole or other private source.
	Water Monitoring	1	1		For each meter (main and sub): 1. Install a pulsed or other open protocol communication output, AND 2. Connect it to an appropriate utility monitoring and management system, e.g. a building management system (BMS), for the monitoring of water consumption or ensure that the system used enables connection to a BMS should one be used in the future. On sites with multiple units or buildings, fit separate submeters on the water supply to the following areas (where present): Each individual unit supplied with water Common areas (covering the supply to toilet blocks) Service areas (covering the supply to outlets within storage, delivery, waste disposal areas etc.) Ancillary or separate buildings to the main development with water supply. Evidence Requirements – M&E A schematic/layout drawing for water distribution within the developed area. (It should indicate meters on each water supply). M&E Performance Spec detailing the above.

Wat 03 -	- Water leak detection				
1	Leak detection system	1	0	1	A leak detection system will be installed capable of detecting a major water leak on the utilities water supply within the buildings, to detect any major leaks within the buildings AND between the buildings and the utilities water supply, to detect any major leaks between the utilities supply and the buildings under assessment. Please note that a BMS is not required to obtain this credit, systems such as the Aqualeak will be compliant.
Wat 04 -	Water efficient equipme	nt			
	Credit	Available	Current	Potential	Comments
1	Water efficient equipment	1	1	0	Identify all water demands from uses other than those listed in Wat 01 that could be realistically mitigated or reduced (e.g. for irrigation, vehicle wash plant/equipment etc The project team should then identify the system(s) or processes to reduce the unregulated water demand of the development and its operation, and demonstrate through either good practice design or specification a meaningful reduction in the total water demand of the building. Planning drawings show water butts for irrigation (drawn off by hand). 10no. butts will provide a total of 3500l.
		3	2	1	Standard Water Credit Total
		0	0	0	Exemplary Water Credit Total
			1.33	0.66	% Water Total (Standard + Exemplary)

Materials

	Credit	Available	Current	Potential	Comments
1	Superstructure	6	4	0	During the Concept Design, demonstrate the environmental performance of the building by carrying out a building LCA on the superstructure design using an IMPACT compliant LCA tool.
					Results must be submitted to the BRE at the end of Concept Design and before planning permission is applied for.
					Evidence Requirements - LCA Consultant
					 The options appraisal summary document Evidence that the LCA options appraisal summary document has been received by the design team and client (meeting minutes, letter of acknowledgement) Evidence of how the LCA design options have informed the design decision-making process (e.g. meeting minutes, documented design development showing how the LCA options have affected the design).
2	Substructure and hard landscaping options	1	1	0	The options appraisal must be achieved before these credits can be awarded. During Concept Design identify opportunities for reducing environmental impacts by carrying out a

,	building types)				hard landscape design options
					Evidence requirements - LCA/LCC consultant
					 Options appraisal summary document Evidence of how the LCA design options have informed the design decision-making process
	Core building services options appraisal during	1	1	0	Option appraisals credit must be achieved before this credit can be considered
	Concept Design (all building types)				During Concept Design identify opportunities for reducing environmental impacts as follows:
	zanamy typosy				 Carry out building LCA options appraisal of at least 3 significantly different core building services design options.
					Evidence requirements - LCA/LCC consultant
					 Options appraisal summary document Evidence of how the LCA design options have informed the design decision-making process
	LCA and LCC alignment (all building types)	1	0	0	Not targeted
					Achieve the options appraisal for Concept Design and achieve Man 02 Life cycle cost and service life planning credits
	Third party verification (all building types) - Exemplary level criteria	1	1	0	Achieve credits one and two. Ensure a suitably qualified third party carries out the building LCA work
Mat 02 - I	Mat 02 Environmental im	pacts from	constructi	on products	- Environmental Product Declarations (EPD)
(Credit	Available	Current	Potential	Comments
	Specification of products with a recognised	1	0	0	Not targeted
6	environmental product declaration (EPD)				Specify construction products with EPD that achieve a total EPD points score of at least 20.
					It is usual for this issue to form part of the ER's however recent assessments of similar projects have shown that this credit is difficult to achieve under 2018. This credit also potentially limits the procurement strategy due to the complexities of the BREEAM scoring mechanism allowing an EPD to be counted in only one classification group to a maximum of 4 points.
	Responsible sourcing of con	nstruction pro	oducts		
(Credit	Available	Current	Potential	Comments

Pre- req	Prerequisite				Mandatory
.59					All timber and timber-based products used on the project are legally harvested and traded timber as per the UK government's Timber Procurement Policy.
1	Enabling sustainable procurement	1	1	0	A sustainable procurement plan must be used by the design team to guide specification towards sustainable construction products and must be in place before Concept Design.
					Evidence Requirements - Client
					Copy of Sustainable Procurement Plan
2	Measuring responsible sourcing	3	2	0	Ensure construction products are sustainably sourced by using suppliers with recognised responsible sourcing certificates or environmental management systems i.e. BES6001, CARES, CSC, FSC, PEFC and SFI.
					The following materials are assessed:
					 Timber Concrete / Cementitious Metals Stone Clay Glass
					Plastic, polymer, resin, paint, chemicals and bituminous Insulation
					Evidence Requirements - Architect
					Completion of the Mat 03 Compliance Proforma to identify the materials that will be present in the building
					Evidence Requirements - Contractor
					Mat 03 Compliance Proforma - identify product name and manufacturer
e1	Measuring responsible sourcing	1	0	0	Not targeted
Mat 05	- Designing for durability		Y		
	Credit	Available	Current	Potential	Comments
1	Protecting vulnerable parts of the building from damage/material	1	1	0	Protection measures must be incorporated into the building's design and construction to reduce damage to the buildings fabric or materials in case of accidental or malicious damage occurring. In addition key exposed building elements must be designed and specified to limit long and short term

	degradation				degradation due to environmental factors.
					Evidence Requirements - Architect
					 Marked up plans/drawings identifying vulnerable areas of the building internally and externally Design drawings/specifications showing protection measures incorporated to prevent damage Schedule identifying measures to protect from material degradation listing applicable building elements, applicable environmental factors, material degradation effects and any measures specified to mitigate the possible degradation.
					A copy of the schedule is available from assessor.
Mat 06	- Material efficiency				
	Credit	Available	Current	Potential	Comments
1	Material efficiency	1	0	0	Not targeted
					This is a time consuming credit requiring evidence of meetings held at RIBA Stages 1 to 5 and subsequent report and has therefore not been targeted.
	481	14	9	0	Standard Materials Credit Total
		3	1	0	Exemplary Materials Credit Total
			1 15.14	0	Exemplary Materials Credit Total % Materials Total (Standard + Exemplary)
Waste	•		<u>'</u>	-	
10000	- Construction waste ma	3	<u>'</u>	-	
10000		3	<u>'</u>	-	
Waste Wst 01	- Construction waste ma	3 anagement	15.14	0	% Materials Total (Standard + Exemplary)

Pre-demolition audit.

Three credits - 3.4m³ (3.2 tonnes)

One credit - 13.3m³ (11.1 tonnes) - targeted Two credits - 7.5m³ (6.5 tonnes)

3

1

1

Construction resource

efficiency

Prepare a compliant RMP covering non-hazardous waste materials (from on-site construction and dedicated off-site manufacture or fabrication including demolition and excavation waste. Credits are awarded for the amount of waste generated per 100m² (gross internal floor area).

Diversion of resources from landfill Diversion of resources Substance of through recovery. Diversion of resource from landfill Diversion of resource f	eted plan must contain
e1 Construction resource efficiency/Diversion of resources from landfill Credits are awarded for the amount of waste generated per 100m² (gross intern ≤1.6m³ (1.9 tonnes) Diversion of resources from landfill Exemplary level 85% volume (90% tonnage) of non-demolition waste 85% volume (95% tonnage) of demolition waste 95% volume (95% tonnage) of excavation waste	al floor area)
Wst 02 - Use of recycled and sustainably sourced aggregates	
Credit Available Current Potential Comments	
Pre-req Prerequisite Not targeted	
1 Project Sustainable 1 0 0 Aggregate points 1 This is a difficult credit to achieve with full responsibility on the contractor to ach	
e1 Project Sustainable 1 0 0 experience contractors have found that the relevant information cannot be obtained to be awarded and as such it has not been targeted.	ned to enable this credit

Wst 03	- Operational waste				
	Credit	Available	Current	Potential	Comments
1	Operational waste	1	1	0	Provide a dedicated space for the segregation and storage of operational recyclable waste generated.
					The space must be
					 Clearly labelled, to assist with segregation, storage and collection of the recyclable waste streams Accessible to building occupants or facilities operators for the deposit of materials and collections by waste management contractors Of a capacity appropriate to the building type, size, number of units (if relevant) and predicted volumes of waste that will arise from daily or weekly operational activities and occupancy rates. Evidence Requirements - Architect Drawings to demonstrate the location of the operational waste facility (and water outlet where applicable) Drawing must include area for recyclable waste, labelling and accessibility Evidence Requirements - Client
Wet 05	- Adaptation to climate ch	ange			Confirmation of type and volume of waste streams
113100	Credit	Available	Current	Potential	Comments
1	Resilience of structure,	1	0	0	Not targeted
·	fabric, building services and renewables installation	,			The aim of this credit is to identify how extreme weather conditions arising from climate change may affect the building's fabric and structure, and to mitigate against these effects. A climate change adaptation strategy appraisal must be conducted using a systematic risk assessment to identify the impacts of expected extreme weather conditions arising from climate change on the
					building over its projected life cycle.
					Evidence Requirements - Architect
					Risk assessment report
e1	Responding to climate change	1	0	0	Not targeted
Wst 06	Design for disassembly	and adaptal	bility		
	Credit	Available	Current	Potential	Comments
1	Design for disassembly and functional	1	1	0	The aim of this issue is to avoid unnecessary materials use, cost and disruption arising from the need for future adaptation works as a result of changing functional demands and to maximise the ability to

	adaptability - recommendations				reclaim and reuse materials at final demolition in line with the principles of a circular economy. A study must be conducted to explore the ease of disassembly and the functional adaptation potential of different design scenarios. Recommendations or solutions must be developed during or prior to Concept Design, that aim to enable and facilitate disassembly and functional adaptation. Evidence Requirements - Architect Copy of disassembly and functional adaptability study.
2	Disassembly and functional adaptability - implementation	1	1	0	First Wst 06 credit must be achieved and updates and change provided during Technical Design, on how the recommendations or solutions have been implemented where practical and cost effective. A building adaptability and disassembly guide also needs to be provided to communicate the characteristics allowing functional adaptability and disassembly to prospective tenants. Evidence Requirements - Architect Copy of Stage 4 Disassembly and functional adaptability study.
		10	6	1	Standard Waste Credit Total
		2	0	0	Exemplary Waste Credit Total
			4.80	0.80	% Waste Total (Standard + Exemplary)

Land Use & Ecology

LE 01 - Site selection

	Credit	Available	Current	Potential	Comments
1	Previously occupied land	1	1	0	At least 75% of the proposed development's footprint is on an area of land which has previously been occupied by industrial, commercial or domestic buildings or fixed surface infrastructure.
					Evidence Requirements - Architect
					Drawings pre and post development depicting at least 75% of the proposed development's footprint on an area of land which has previously been occupied
2	Contaminated land	1	0	0	Not targeted
					A site investigation must be undertaken to determine whether the land has been deemed as affected by contamination. The report must identify the options for remediating sources of contamination and the client must confirm that remediation of the site will be carried out in accordance with the remediation strategy for this credit to be awarded.

LE 02 -	Ecological risks and oppo	ortunities			Contaminated Land Report and remediation report and where applicable a Geotechnical and Geo-environmental interpretative report
	Credit	Available	Current	Potential	Comments
Pre- req	Prerequisite - Statutory obligations				Pre-requisite achieved where the client or contractor confirms compliance is monitored against all relevant UK and EU or international legislation relating to the ecology of the site.
					Evidence Requirements - Client
					Provide a letter confirming that compliance is monitored against all relevant UK and EU or international legislation relating to the ecology of the site.
1	Survey and evaluation/Determining ecological outcomes	2	2	0	Route 2 (Ecologist) - Prior to the completion of the Preparation and Brief project stage, an appropriate level of survey and evaluation has been carried out by a suitably qualified ecologist to determine the ecological baseline of the site, taking account of the immediate surrounding area to establish: a) Current and potential ecological value and condition of the site, and related areas within the zone of influence; b) Direct and indirect risks to current ecological value; c) Capacity and feasibility for enhancement of the site's ecological value and, where relevant, areas within the zone of influence. Recommendations and data collected from the survey are shared with appropriate project team members to influence decisions made for activities during site preparation, design and construction works. Evidence Requirements - Ecologist Completion of GN40:BREEAM Ecology Assessment Issues Reporting Template for Route 2 Pages 17 - 30 Phase 1 Ecology Report Ecologist CV
e1	Wider site sustainability - Exemplary level criteria	1	0	0	Not targeted
LE 03 -	Managing impacts on eco	ology			
	Credit	Available	Current	Potential	Comments
Pre- req	Prerequisite - Ecological risks and opportunities	v.			LE 02's 'Survey and evaluation and Determining ecological outcomes criteria have been achieved.
1	Planning and measures	1	1	0	Further planning to avoid and manage negative ecological impacts on-site is carried out early enough to

2	Managing negative impacts	2	2	0	influence the concept design and design brief as well as site preparation planning (typically Concept Design stage). Evidence Requirements - DT Architect, Client, Planning Consultant, Ecologist to provide meeting minutes/ email threads/ record of telephone conversations to show liaison between the Ecologist and the design team. Evidence Requirements - Contractor Completion of GN40:BREEAM Ecology Assessment Issues Reporting Template for Route 2 Pages 17 - 30 The project team must follow the hierarchy of avoid, protect, reduce or limit, compensate when making decisions about issues that have an impact on ecology, wherever possible limiting disruption and disturbance to local wildlife or ecological systems. Where disruption is likely to arise during construction
					works and operation of the asset, the focus should be on minimising disruption to maximise value and ensure that it is sustainable for the longer term. Any features of ecological value must be identified and protected in accordance with best practice guidelines during development works. There must be either no overall loss of ecological value or the ecological loss has been minimised. Evidence Requirements - Ecologist Confirmation that any features of ecological value will be identified and protected in accordance with best practice guidelines during development works - basically a copy of the wildlife protection plan for construction. Confirmation that there was either no overall loss of ecological value or the ecological loss has been minimised. Completion of GN40:BREEAM Ecology Assessment Issues Reporting Template for Route 2 Pages 17-30
LE 04 -	Ecological change and er			D (4) .	
	Credit	Available	Current	Potential	Comments
Pre- req	Prerequisite - Managing negative impacts on ecology				The client or contractor confirms compliance is monitored against all relevant UK, EU or international legislation relating to the ecology of the site.
					Criteria 2-3 in LE03 have been achieved,

					Evidence Requirements - Client/Contractor or Ecologist Confirm compliance is monitored against all relevant UK and EU or international legislation relating to ecology of the site
1	Change and enhancement of ecology / Ecological enhancement	1	1	0	The project team must take into consideration data collated and shared whilst liaising with representative stakeholders and implement the solutions and measures selected in a way that enhances ecological value either on site and where this is not feasible off site with the immediate surround area. Evidence Requirements - Landscape Architect Landscape Plan Planting Schedule Evidence Requirements - Ecologist BREEAM Change in Ecological Value tool Completion of GN40:BREEAM Ecology Assessment Issues Reporting Template for Route 2 Pages 17-30
2	Change and enhancement of ecology	3	2	0	Up to three credits are awarded based on the calculation of the change in ecological value occurring as a result of the project. • Minimising loss of ecological value (one credit - percentage score of 75-94) • No net loss of ecological value (two credits - percentage score of 95-104) • Net gain of ecological value (three credits - percentage score of 105-109) Evidence Requirements - Landscape Architect • Landscape Plan • Planting Schedule Evidence Requirements - Ecologist • BREEAM Change in Ecological Value tool • Completion of GN40:BREEAM Ecology Assessment Issues Reporting Template for Route 2 Pages 17-30
e1	Change and enhancement of ecology	1	0	0	Not targeted

	- Exemplary level criteria				Significant net gain of ecological value (percentage score of 110 or above)					
LE 05 -	E 05 - Long term ecological management and maintenance									
	Credit	Available	Current	Potential	Comments					
Pre- req	Prerequisite - Statutory obligations, planning and site implementation				The client or contractor has confirmed that compliance is being monitored against all relevant UK, EU and international standards relating to the ecology of the site. Criteria 8 in LE 03 has been achieved, and at least one LE 04 'enhancement of ecology' credit has been achieved.					
1	Management and maintenance throughout the project / Landscape and ecology management plan	2	2	0	Develop a landscape and ecology management plan, or equivalent in accordance with BS42020:2013 Section 11.1 covering as a minimum the first five years after project completion. Evidence Requirements - Ecologist/Landscape Architect • Copy of Landscape and Ecology Management Plan					
					 Confirmation that the plan will be handed over to the tenant/occupier/building manager Completion of GN40:BREEAM Ecology Assessment Issues Reporting Template for Route 2 Pages 17-30 					
		13	11	0	Standard Land Use & Ecology Credit Total					
		2	0	0	Exemplary Land Use & Ecology Credit Total					
			16.07	0	% Land Use & Ecology Total (Standard + Exemplary)					

Pollution

Pol 03 - Flood and surface water management

	Credit	Available	Current	Potential	Comments
1	Flood resilience	2	2	0	An appropriate consultant is appointed to carry out and demonstrate the development's compliance with all criteria.
					Low flood risk - two credits A site-specific flood risk assessment (FRA) confirms the development is in a flood zone that is defined as having a low annual probability of flooding. The FRA must take all current and future sources of flooding into consideration. The Environment Agency's flood map shows the development site is in a low flood risk area Evidence Requirements - Drainage Engineer • FRA
2	Surface water run-off	2	2	0	Prerequisite - Surface water run-off solutions must be bespoke