

150Ø uPVC PERFORATED FILTER COLLECTION DRAIN 100mmØ PERFORATED UPVC FLEXIBLE PIPE

FILTER DRAIN

CONSTRUCTION TO BE TANKED WITH A \_

1mm THICK IMPERMEABLE MEMBRANE

300mm THICK DfT

TYPE 3 SUB BASE

TYPICAL SECTION THROUGH PERMEABLE ASPHALT **SCALE 1:20** 

- 1. When foundation is more than 450mm above drain do not
  - 2. Joint Filler to be plastazote or similarly approved.
  - 3. 12mm diameter chord for 100mm drainage pipes with 150mm
  - 4. 25mm diameter chord filler for 150mm drainage pipes with
  - 225mm diameter casing.
  - 5. Where drainage pipes under buildings have less than 300mm cover they shall have 150mm concrete encasement.

SPECIFICATION.

THIS DRAWING TO BE READ IN CONJUNCTION WITH ALL OTHER RELEVANT

2. IT IS THE CONTRACTOR'S RESPONSIBILITY TO CHECK ALL DIMENSIONS ON

4. ALL DIMENSIONS ARE IN MILLIMETRES, UNLESS NOTED OTHERWISE.
5. ALL LEVELS ARE IN METRES, UNLESS NOTED OTHERWISE.

ENGINEER'S AND SPECIALIST'S DRAWINGS TOGETHER WITH THE APPROPRIATE

DIMENSIONS <u>MUST NOT</u> BE SCALED FROM THIS DRAWING. ANY DISCREPANCIES TO BE BROUGHT TO THE IMMEDIATE ATTENTION OF THE ENGINEER IN

T2 05-10-22 DRL Project title updated DRL T1 10-06-22 DRL Issued for Tender PJB Rev Date By Description Appd Revisions

Status **TENDER** 



Tier Consult Ltd. Richmond House Sandpiper Court Chester Business Park Chester | CH4 9QZ t: 01244 684900

TRITAX SYMMETRY

SYMMETRY PARK, OXFORD

DRAINAGE CONSTRUCTION DETAILS -SHEET 2

As Shown @A1 DRL T2 Oct'21

Drawing Ref :
Project no|Originator|Volume|Level|Type|Role|Number T/21/2407

55-03