



## Water Use Assessment

## **Design Stage - Calculation Report**

Certificate Ref: BE44967245 Performance Target: 110 (litres / person / day)

Issued: 01 February 2023 Building Regulations Part G - 110l

Hempton Road - Phase 2 - HT S3 Number of Bedrooms: 3

Burrington Estates Occupancy for Calculation Purposes 4

Design Stage

Installation Type	Unit	Capacity/ Flow Rate	Use Factor	Fixed use (I/p/day)	Total Use (I/p/day)
WC's	Volume (I)	3.50	4.42	0.00	15.47
Taps Exc. Kitchen	Flow Rate	5.00	1.58	1.58	9.48
Baths	(1)	180.00	0.11	0.00	19.80
Showers	(I/s)	8.00	4.37	0.00	34.96
Kitchen Taps	(I/s)	8.00	0.44	10.36	13.88
Washing Machines	(I/kgdry)	8.17	2.10	0.00	17.16
Dishwashers	(l/place)	1.25	3.60	0.00	4.50
Waste Disposal	(I/s)				0.00
Water Softener	(I/s)				0.00
Total Calculated Water Use (I/p/day)					115.25
Grey/Rainwater Reused (I)					0.00
Normalisation Factor					0.91
Total Water Consumption (I/p/day)					104.88
External Water Use Allowance (I)					5.00
Total Consumption Part G (I/p/day)					109.88
Part G Reg Assessment Result					Pass <b>√</b>

The calculation methodology uses the water consumption figures provided from manufacturers' product details. Where details have not been provided, assumed figures have been used to achieve compliance. These must be met in order to satisfy the Part G Calculation for Hempton Road - Phase 2 - HT S3. The calculation methodology is to be used to assess compliance against the water performance targets in Regulation 36. It is not a design tool for water supply and drainage systems. It is also not capable of calculating the actual potable water consumption of a new dwelling. Behaviour and changing behaviour can also have an effect on the amount of potable water used throughout a home.



Bishops Court, 17a The Broadway, Old Hatfield Hertfordshire, AL9 5HZ, T: 0330 223 6960 | E: info@briaryenergy.co.u

## Appliance/Usage Details

,	_								
Taps (Excluding Kitchen	Taps)			Showers					
Tap Fitting Type	Flow Rate	Quantity	Total per	Shower fitting	Flow Rate	Quantity	Total per		
	Litres/Min	(No.)	Fitting type	Type	Litres/Min	(No.)	Fitting type		
Bathroom sink mixer taps	5	3	15.00	Shower over Bath	8	1	8.00		
				Shower	8	1	8.00		
Total No. of Fittings (No.)			3	Total No. of Fittings (No.)			2		
Total Flow (I/s)			15.00	Total Flow (I/s)			16.00		
Maximum Flow (I/s)			5.00	Maximum Flow (I/s)			8.00		
Average Flow (I/s)			5.00	Average Flow (I/s)			8.00		
	Veighted Average Flow (I/s)			Weighted Average Flow (I/	5.60				
Flow for Calculation (I/s)	., -,		3.50 5.00	Flow for Calculation (I/s)	8.00				
Baths				WCs					
Bath Type	Capacity to	Quantity	Total per		Full Flush	Part Flush	Quantity (No)		
, , , , , , , , , , , , , , , , , , ,	Överflow	`(No.) ´	Fitting type	WC Type	Volume	Volume	, , , ,		
Bath	180	1	180.00	Dual flush toilet	4.5	3	3		
		<del></del>							
Total No. of Fittings (No.)			1						
Total Capacity (I)			180.00	Total number of fittings		3			
Maximum Capacity (I)			180.00	Average effective flushing volume			3.50		
Average Capacity (I)			180.00	Twerage effective hashing volume			0.50		
Weighted Average Capac	·i+v/(I)		126.00						
Capacity for Calculation (			180.00						
Capacity for Calculation (	1)		100.00						
Dishwashers				Washing Machines					
Dishwasher Type	L per Place	Quantity	Total per	Washing Machine	L per Kg	Quantity	Total per		
71	Setting	`(No.) ´	Fitting type	Type	Dry Load	`(No.) ´	Fitting type		
Dishwasher	1.25	1	1.25	Washing Machine	8.17	1	8.17		
				0 11					
Total No. of Fittings (No.)			1	Total No. of Fittings (No.)	1		1		
Total Consumption (I)			1.25	Total Consumption (I)			8.17		
Maximum Consumption (				Maximum Consumption (I) 8.17					
Average Consumption (I/s			1.25	Average Consumption (I/s)			8.17		
Weighted Average Consu				Weighted Average Consur	5.72				
Consumption for Calculat			0.88 1.25	Consumption for Calculation (I/s)			8.17		
	(,, 5)		1.20		o (., o,		0.17		
Kitchen Taps				Other Fittings					
Tap Fitting Type	Flow Rate	Quantity	Total per	Waste Disposal Y/N		N			
7,1	Litres/Min	(No.)	Fitting type	Water softener					
Kitchen Tap	8	1	8.00	Consumption beyond 4% I	/p/d				
Utility Tap	8	<u> </u>	5.55	2	- 1		1		
				Use of grey water and har	vested rainw	ater			
Total No. of Fittings (No.)			1	or or or mader and ful	S. S				
Total Flow (I/s)			8.00	Total Grey water from WH	HB taps (I)				
Maximum Flow (I/s)			8.00	Total Available Grey Water Supply (I)					
Average Flow (I/s)			8.00	Possible Demand (I)					
Weighted Average Flow (	I/s)		5.60	Grey/Rain Installed Capac					
Flow for Calculation (I/s)	1, 5,		8.00	Figure for Calculation lit/person/day					
. 1577 TOT Carculation (1/3)			0.00	gare ror calculation III/p	C. 3017, day		J		