



## Water Use Assessment

## **Design Stage - Calculation Report**

Certificate Ref: BE44967643 Performance Target: 110 (litres / person / day)

Issued: 01 February 2023 Building Regulations Part G - 110l

Hempton Road - Phase 2 - HT S4 Number of Bedrooms: 3

Burrington Estates Occupancy for Calculation Purposes 4

Design Stage

Installation Type	Unit	Capacity/ Flow Rate	Use Factor	Fixed use (I/p/day)	Total Use (I/p/day)
WC's	Volume (I)	3.50	4.42	0.00	15.47
Taps Exc. Kitchen	Flow Rate	5.00	1.58	1.58	9.48
Baths	(1)	180.00	0.11	0.00	19.80
Showers	(l/s)	8.00	4.37	0.00	34.96
Kitchen Taps	(I/s)	8.00	0.44	10.36	13.88
Washing Machines	(l/kgdry)	8.17	2.10	0.00	17.16
Dishwashers	(l/place)	1.25	3.60	0.00	4.50
Waste Disposal	(I/s)				0.00
Water Softener	(I/s)				0.00
Total Calculated Water Use (I/p/day)		•	•		115.25
Grey/Rainwater Reused (I)					0.00
Normalisation Factor					0.91
Total Water Consumption (I/p/day)					104.88
External Water Use Allowance (I)					5.00
Total Consumption Part G (I/p/day)					109.88
Part G Reg Assessment Result					Pass <b>√</b>

The calculation methodology uses the water consumption figures provided from manufacturers' product details. Where details have not been provided, assumed figures have been used to achieve compliance. These must be met in order to satisfy the Part G Calculation for Hempton Road - Phase 2 - HT S4. The calculation methodology is to be used to assess compliance against the water performance targets in Regulation 36. It is not a design tool for water supply and drainage systems. It is also not capable of calculating the actual potable water consumption of a new dwelling. Behaviour and changing behaviour can also have an effect on the amount of potable water used throughout a home.



Bishops Court, 17a The Broadway, Old Hatfield Hertfordshire, AL9 5HZ, T: 0330 223 6960 | E: info@briaryenergy.co.u

## Appliance/Usage Details

Taps (Excluding Kitchen	Taps)			Showers						
Tap Fitting Type	Flow Rate	Quantity	Total per	Shower fitting	Flow Rate	Quantity	Total per			
rap ritting rype	Litres/Min	(No.)	Fitting type	Type	Litres/Min	(No.)	Fitting type			
Bathroom sink mixer taps		2	10.00	Shower over Bath		1	8.00			
battil Ootti Sirik Illixer taps	)		10.00		8		0.00			
				Shower	8					
Total No. of Fittings (No.)			2	Total No. of Fittings (No.)			1			
Total Flow (I/s)			10.00	Total Flow (I/s)			8.00			
Maximum Flow (I/s)			5.00	Maximum Flow (I/s)			8.00			
Average Flow (I/s)			5.00	Average Flow (I/s)			8.00			
Weighted Average Flow (	1/c)		3.50	Weighted Average Flow (I/s)			5.60			
	1/3)									
Flow for Calculation (I/s)  5.00 Flow for Calculation (I/s)							8.00			
Baths				WCs						
Bath Type	Capacity to	Quantity	Total per		Full Flush	Part Flush	Quantity (No)			
Datif Type	Overflow	(No.)	Fitting type	WC Type	Volume	Volume	Qualitity (110)			
Dath	180			Dual flush toilet	4.5		2			
Bath	180	1	180.00	Duai nush tollet	4.5	3				
Total No. of Fittings (No.)			1							
Total Capacity (I)			180.00	Total number of fittings	2					
Maximum Capacity (I)			180.00	Average effective flushing	3.50					
Average Capacity (I)			180.00							
Weighted Average Capac	ity (I)		126.00							
Capacity for Calculation (			180.00							
Capacity for Calculation (	.1/		100.00							
Dishwashers				Washing Machines						
Dishwasher Type	L per Place	Quantity	Total per	Washing Machine	L per Kg	Quantity	Total per			
2.6dee,pe	Setting	(No.)	Fitting type	Type	Dry Load	(No.)	Fitting type			
Dishwasher	1.25	1	1.25	Washing Machine	8.17	1	8.17			
Distiwastici	1.23	1	1.23	VVasining iviacinine	0.17		0.17			
Total No. of Fittings (No.)			1	Total No. of Fittings (No.)			1			
Total Consumption (I)			1.25	Total Consumption (I)			8.17			
Maximum Consumption (	1)		1.25				8.17			
				Maximum Consumption (I)						
Average Consumption (I/s			1.25	Average Consumption (I/s)			8.17			
Weighted Average Consu			0.88	Weighted Average Consur			5.72			
Consumption for Calculate	tion (I/s)		1.25	Consumption for Calculati	on (l/s)		8.17			
Vitaban Tana				Other Fittings						
Kitchen Taps	Flave Del	Our and the	Takalaran	Other Fittings		N.I				
Tap Fitting Type	Flow Rate	Quantity	Total per	Waste Disposal Y/N		N				
	Litres/Min	(No.)	Fitting type	Water softener			1			
Kitchen Tap	8	1	8.00	Consumption beyond 4% I	/p/d					
Utility Tap	8									
				Use of grey water and har	vested rainw	ater				
Total No. of Fittings (No.)			1							
Total Flow (I/s)			8.00	Total Grey water from WHB taps (I)						
Maximum Flow (I/s)			8.00	Total Available Grey Water Supply (I)						
Average Flow (I/s)			8.00	Possible Demand (I)						
Weighted Average Flow (	1/c)		5.60	Grey/Rain Installed Capacity (I)						
Flow for Calculation (I/s)	1/3/			8.00 Figure for Calculation lit/person/day						
1 10W 101 Calculation (1/5)			0.00	.00   Tigure for Carculation filt/person/day []						