Banbury (S38) - Street Lighting Schedule 592/101 (Drawing 592/001) - Oxfordshire County Council Standard Drg's - HSD1300-006. OCC File Reference Number: TBC
24th May 2023

Unit Ref	Lighting Design Class	Column Height	Column Type	Lantern Mounting	Lantern Tilt	Door Lock	Planting Depth	Lantern Manufacturer/Model	Rear Shield	Canopy Colour	Switch Control	NEMA Socket	LED Driver	Dimming Regime	UMSUG Code Switch Regime	Double Pole Isolator	Fuse	Lantern to Isolator Cabling	Paint Specification	Column Paint Colour	Electrical Service Type	Highway/Private Ownership	Column Setback Requirements
S1	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	Back of Footpath
S2	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	Back of Footpath
S3	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	Back of Footpath
S4	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	Back of Footpath
S5	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	0.8m behind c/way in adoptable parcel
S6	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	0.8m behind c/way in adoptable parcel
S7	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	0.8m behind c/way in adoptable parcel
S8	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	0.8m behind c/way in adoptable parcel
S9	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	Back of Footpath
S10	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	Back of Footpath
S11	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	0.8m behind c/way in adoptable parcel
S12	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	Back of Footpath
S13	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	0.8m behind c/way in adoptable parcel
S13	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	0.8m behind c/way in adoptable parcel
S14	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	0.8m behind c/way in adoptable parcel
S15	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	0.8m behind c/way in adoptable parcel
S16	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	0.8m behind c/way in adoptable parcel
S17	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	0.8m behind c/way in adoptable parcel
S18	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	0.8m behind c/way in adoptable parcel
S19	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	0.8m behind c/way in adoptable parcel
S20	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	Back of Footpath
S21	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	Back of Footpath
S22	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	Back of Footpath
S23	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	Back of Footpath
S24	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	Back of Footpath
S25	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	0.8m behind c/way in adoptable parcel
S26	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	0.8m behind c/way in adoptable parcel
S27	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	0.8m behind c/way in adoptable parcel
S28	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	0.8m behind c/way in adoptable parcel
S29	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	0.8m behind c/way in adoptable parcel
S30	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	0.8m behind c/way in adoptable parcel
S31	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	0.8m behind c/way in adoptable parcel
S32	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	Back of Footpath
S33	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	Back of Footpath
S34	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	Back of Footpath
S35	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	Back of Footpath
S36	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	Back of Footpath
S37	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	0.8m behind c/way in adoptable parcel
S38	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	Back of Footpath
S39	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	0.8m behind c/way in adoptable parcel
S40	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	0.8m behind c/way in adoptable parcel
S41	P4	6m	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	1.0m	DW Windsor Kirium Pro Mini 16LED WW 3K D4 550mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	0.8m behind c/way in adoptable parcel
FP1	P4	5m (R&L)	BS EN 40 BD94/07 (Style 2 drg (HSD1300-006)	Post Top	0 Degrees	Triangular	0.8m	DW Windsor Kirium Pro Mini 8LED WW 3K A1 500mA	N	RAL 6013 (Reed Green)	Zodion Super 6 35 Lux On / 18 Lux Off	One Piece 7 Pin	Philips Xiatanium	Pre-set to dim to 50% light output between 10:00pm to 6:00am	DB3	Charles Endirect secondary isolation unit as shown on OCC standard detail HSD14000-005	6A - BS88 MD Fuse	7.25m of 3 core 1.5mm² circular flex H05VV-F temperature range -15°C to + 70°C	Dacrylite Dacsil 2-Pack Polysiloxane Finish	RAL 6013	Unmetered Direct DNO	Highway Adoptable	Back of Footpath