Product specification Composite doors



THE JACOBEAN B-RATED SPECIFICATION (A-RATED AVAILABLE)

Frame profile

Choice of:

- Standard (EWS 032)
- Large (EWS031)

Reinforcements

- PVC-U Thermal Inserts

Accreditations

- Secured By Design (subject to specification)
- PAS 23/24
- BM Trada Q Mark

Glass options

- Triple-glazed and double glazed options
- Choice of leading colour

Colour options

Standard door colours

Contemporary door colours










Door frame colours















Furniture

- Letterplates, handles, chains, spy-holes, numbers and knockers
- Choice of White, Gold, Chrome, Satin Silver and Satin Black stainless steel finishes*, backed by 25-year guarantee (*excludes White and Satin Black)

Min / max sizes

Doors with large outer frame

Width		Heig (ali low-th			Height (PVC-U bottom)	
Min	Max	Min	Max	Min	Max	
860	1012	1979	2089	2021	2130	
		, <u>1</u>		i	V	
If door has GRP side panel and an aluminium low-					If door has GF	

Doors with standard outer frame

threshold, min height = 2020. All heights are reduced by 3mm if open out aluminium low-threshold

Width		Height (ali low-threshold)			Height (032 full outer)		ght reshold)
Min	Max	Min	Max	Min	Max	Min	Max
830	982	1964	2074	1991	2100	2006	2115
		1			1		7
threshold, r	min height =	= 2005. All he	aluminium low ights are	par	oor has GRF nel and PVC- y beight - 20	U bottom,	032 is 15mm smalle on both faces

panel and PVC-U bottom,

max height = 2121

GRP side panels

Min width	Max width	Height
410	475	To suit door


All side lights are separate. Sizes include outer frame and coupler

Transom height from bottom of door

Alumi		PVC-U bottom		
Min	Max	Min	Max	
1945	2054	1971	2080	

Dimensions to centre of transom, Doors over 2500mm will have separate top lights

Glazing sizes



The Jacobean

Vertical cassette / Three Cassette option

203mm x 912mm /

203mm x 150mm -

203mm x 460mm -

203mm x 150mm