




T1 12 OFF - 69 kg/ply



SP1 1 OFF - 69 kg/ply



GP1 1 OFF - 77 kg/ply



This drawing and the copyright therein is the property of H & S Timber Systems and MUST NOT be reproduced in any form or put to any other use. As a condition of the supply of this drawing, it may not be used for the purpose of obtaining quotes or offers from any other source.

This Roof Layout is provided to show truss location only. Any structural ancillary timbers provided with trusses are based on span tables shown in the Bldg Regs Approved Document 'A'. They are not designed by H & S Timber Systems. Ancillary Timbers are shown on our layouts to achieve as near as possible correct loading for multi/girder trusses. H & S Timber Systems are acting as the Trusses Rafter Designer only as stated in our quotation. It is the Building Designers responsibility to oversee the design of the roof as a whole.

**GENERAL NOTES**

1. Trussed rafters MUST NOT be spaced at more than 600mm max c/c unless otherwise noted
2. Trusses MUST NOT be cut U.D.N.
3. All soffit and Fascia cuts by others.
4. Maxm 300 litre water tank (over 4 trusses only) to be supported on bearers similar to that shown in BS5268 PT3 1998 in truss bays indicated only. Tank supports by others.
5. Access hatches to be trimmed between two trusses at centres shown on plan
6. To maintain uniformity of roof profile the truss clg joint splices MUST BE in line through the roof space
7. All loose infill material is supplied in Ex stock lengths for cutting to length on site by erectors.

**HANGER LEGEND & FIXINGS**

M = Mono truss shoe with minm 75mm bearing  
G = Girder truss shoe (G.T.S)  
MX = Maxi bolted girder hanger to be fully nailed and bolted (M12 bolts)  
J = Infil Joist hangers long or short leg  
B = Heavy duty Bolted hanger (M20 bolts)  
S = masonry hangers (S.P.H) we do not recommend supporting girder trusses with masonry hangers.

Single truss fixed at each w/plt using 1 no truss clip. Multi truss fixed using pairs of framing anchors. Raised tie trusses fixed using either truss clips, framing anchors or Glide shoes dependent on truss calculations. ALL metalwork fixings to be fully nailed with 3.75x32mm lg sq twist nails or similar. Infil to be skew nailed using 2 no minm 4mm dia x 100mm lg galv wire nails as BS5268

**BRACING LEGEND AND FIXINGS**

RB = Rafter bracing  
CB = Ceiling bracing  
WB = Web chevron bracing  
LW = Web compression brace  
in situations where truss has single rafter the web compression brace is to be nailed along length of web to form 'T' brace

All bracing to be Minm 22x97 sawn timber, to be twice nailed at each crossover with 3.35x65mm galv round wire nails in accordance with BS5268, pt3 1998. Garage roofs taken to have plasterboard clg, if not diagonal ceiling bracing is required

**ROOF LOADINGS - concrete interlocking**

Rafter Dead = 685 N/m<sup>2</sup> (58kg/m<sup>2</sup> tile)  
Rafter Live = 750 N/m<sup>2</sup>  
Ceiling Dead = 250 N/m<sup>2</sup>  
Ceiling Live = 250 N/m<sup>2</sup>  
Attic floor load = 1500 N/m<sup>2</sup>  
Rafter restraint 400mm maxm

Trusses Ex 38mm - untreated  
Excluded from our quotation and supply are All connections to masonry and steelwork. Nails and fixings for metalwork and bracing. Bracing/Wingirders to stabilise walls. Masonry hangers to support girder trusses. Dormer cheek finishes and flat roof finishes. Site measuring, inspections or surveys. Second fix items ie soffit, fascia etc..

Rev	Date	REVISIONS Comment	Init
A	06.06.19	Plot handed	jc
B	27-6-19	Panel amendment	jc

Harlow Timber Systems Ltd.  
Walker Road, Bardon Hill,  
Leics. LE67 1TU

SITE :New Development,  
Cotefield Drive Bodicote,  
Oxfordshire

LOADS:Tiles=685 Snow=481 N/m<sup>2</sup>

SPACING :600mm

Drawn : James Cave

Checked :

DATE : 27-6-2019

PROJECT : Crest Nicholson

DRG NO : K11501/AH2B WC [P